


REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED



SPECIFICATIONS

Frequency Range: 7.2–8.5 GHz
 Insertion Loss: 0.8dB Max.
 Isolation: 18dB Min.
 VSWR Input/Output: 1.40:1/1.35:1 Max.
 Amplitude Balance: ± 0.3 dB Max.
 Phase Balance: ± 6 Deg. Max.
 Power: 30W (vswr@1.2)

MATERIAL: 		MCLI MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM		SCALE:	N/A
		UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR [mm] (MILLIMETERS) FRACTIONS: $\pm 1/64$ DECIMALS: $\pm 0.01 \pm 0.005$ ANGLE: $\pm 1/2^\circ$		SHEET:	N/A
DRAWN: Paiboon Luekhamhan DATE: 06-29-1999		DRAWING TITLE: 4-WAY POWER DIVIDER			
APPROVED: T. Nguyen DATE: 06-29-1999		PART NO. PS4-18			
		CAGE CODE:	SIZE: A	REV: N/A	DWG NO.
		OD2L5	DO NOT SCALE THE DRAWING		80184