




							THIS DRAWING CONTAINS CONFIDENTIAL INFORMATION PROPRIETARY TO SAN-TRON, INC. IT MUST NOT BE REPRODUCED OR DISCLOSED TO OTHERS OR USED IN ANY OTHER WAY, IN WHOLE OR PART EXCEPT AS AUTHORIZED IN WRITING BY SAN-TRON, INC.			 SAN-TRON, INC. 4 NEWBURYPORT TPK. IPSWICH MA USA 01938 TEL: 978 - 356 -1585 FAX: 978 - 356 -1573 WWW.santron.com E MAIL: santron@santron.com			
							UNLESS OTHERWISE SPECIFIED: ALL DIMENSIONS ARE IN INCHES. ALL DIMENSIONS ARE AFTER PLATING. .XXX= ±.005 ALL MACHINED SURFACES $\sqrt{\text{MAX.}}$.XX= ±.01 ANG.±1/2° FRACTIONAL= ±1/64  .004 MAX. TIR.  AXIS .001			TITLE eSMA PANEL JACK, DIRECT SOLDER FOR T-FLEX 402			
C	ADD PIM PERFORMANCE		MIX	9/23/11	FSH	FSH				MATERIAL: SEE NOTE 2.0		FINISH: SEE TABLE	
B	HEX DIE FROM .213 TO .231		MIX	10/27/08	FSH	FSH				CAGE CODE: 50896		DWG NO. OL-1204-06-1	
A	RELEASE		NEW	11/16/07						SCALE X:X		REV. C	
Rev.	Revisions		Disp.	Date	Dwn.	Appd.	 THIRD ANGLE PROJECTION						
		Ref.: SK-	REMOVE ALL BURRS AND SHARP EDGES .005 MAX.		INTERPRET PER ASME Y14.5M-1994								
							DWN	JTH	11/16/07				
							CHKD	SJS	11/19/07				
							APPR	FSH	11/20/07				