


REVISIONS				
ZONE	REV	DESCRIPTION	Date	APPROVED



SPECIFICATIONS

Frequency Range: 18–22GHz
 Isolation: 21dB Min.
 Insertion loss: 0.6dB Max.
 VSWR: 1.20:1 Max.
 Circulator Power: 25W Avg, 250W Peak.
 Operating Temperature: –54°C to +85°C

MATERIAL: 		MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM		SCALE: N/A	
				SHEET: N/A	
DRAWN: Paiboon Luekhamhan		DATE: 05-17-2010		PROPERTY NOTICE: THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICROWAVE COMMUNICATIONS LABORATORIES INC. (MCLI)	
APPROVED: T. Nguyen		DATE: 05-17-2010		DRAWING TITLE: COAXIAL CIRCULATOR	
		CAGE CODE: OD2L5		PART NO. CS-86	
				DO NOT SCALE THE DRAWING	
				SIZE: A REV: N/A DWG NO. 84803	