

75 Ohm TNC Male to BNC Female Adapter



TECHNICAL DATA SHEET

PE9631

75 Ohm TNC Male to BNC Female Adapter

Configuration

Connector 1 TNC Male
Impedance 1 75 Ohms
Connector 2 BNC Female
Impedance 2 75 Ohms
Adapter Design Standard
Body Style Straight

Mechanical Specifications

Size

Length, in [mm] 1.234 [31.34] Width/Dia., in [mm] 0.59 [14.99]

Connector 1

TNC Male Type Inner Conductor Material and Plating Brass, Gold Inner Conductor Plating Specification 50μ in. minimum Coupling Nut Material and Plating Brass, Nickel Coupling Nut Plating Specification 100µ in. minimum Body Material and Plating Brass, Nickel **Body Plating Specification** 100µ in. minimum Dielectric Type Teflon

Connector 2

Type BNC Female
Inner Conductor Material and Plating Brass, Gold
Inner Conductor Plating Specification 50μ in. minimum
Body Material and Plating Brass, Nickel
Body Plating Specification 100μ in. minimum
Dielectric Type Teflon

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

Plotted and Other Data

Notes: Values at 25 °C, sea level

URL: http://www.pasternack.com/tnc-male-bnc-female-straight-adapter-pe9631-p.aspx

75 Ohm TNC Male to BNC Female Adapter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

ISO 9001 : 2008 Registered

PE9631 CAD Drawing75 Ohm TNC Male to BNC Female Adapter

