

DESCRIPTION

This class AB LDMOS module is designed for both military and commercial applications. It is capable of supporting any signal type and modulation format, including but not limited to 3-4G telecom, WLAN, OFDM, DVB, and CW/AM/FM. The latest device technologies and design methods are employed to offer high power density, efficiency, and linearity in a small, lightweight package.

**FEATURES**

Over / Under / Reverse Voltage Protection
Reflected Power Measurement
Temperature Output
Optional Heatsink

Forward Power Measurement
High Speed T/R Switching Control
Manual Gain Control
Manual or Automatic Tx/Rx Switching Available

Specifications subject to change without notice. Typical performance at +28VDC at 25°C in a 50Ω system

Tx SPECIFICATIONS				
PARAMETER	MIN	TYP	MAX	UNIT
Operating Frequency	2300		2500	MHz
PSat Power Output	+45.0	+46.0		dBm
Gain	46.0	47.0		dB
Gain Flatness		1.0	1.5	dB
Input Return Loss	-16	-18		dB
Operating Voltage	+24	+28	+30	VDC
Current Draw		2.0	3.0	A
Tx / Rx Switching Time		1.0	2.0	μs

Rx SPECIFICATIONS				
PARAMETER	MIN	TYP	MAX	UNIT
P1dB Power Output		+5.0		dBm
Gain		11.0		dB
Gain Flatness		0.5	1.3	dB
Noise Figure		2.5	4.0	
OIP3		+15.0		dBm
Input Return Loss	-8	-10		dB
Current Draw			100.0	mA


MECHANICAL		
PARAMETER	VALUE	UNIT
Dimensions (L x W x H)	5.3 x 3.25 x 0.57	in
RF Connectors (Input / Output)	SMA-F / SMA-F	--
DC / Control Connector	15 Pin Micro-D	--
Cooling	Baseplate Conduction - Optional Heatsink Available	--
Mounting	4-40 Thru Holes	--
Weight	12	oz
Weight With Heatsink	22	oz


ENVIRONMENTAL / PROTECTIONS			
PARAMETER	MIN	MAX	UNIT
Operating Temp. (Housing Temp.)	-40	+85	°C
Storage Temp Range	-60	+100	°C
Humidity Range	0-100		%
Altitude	0-30,000		ft.
Shock / Vibration	MIL-STD-810 and equivalents		--
Max RF Input	+2		dBm
Load VSWR @ P1dB	Open / Short Output Protection		--
PA Baseplate Shutoff Temperature	+90		°C



DC / CONTROL PINS		
PIN LABEL	NAME	DESCRIPTION
A1	GND	Ground
1	TEMP	Temp Monitor: Temp in DegC = (Vout - 0.5V) / 10
2	Tx/Rx	Tx / Rx Switching (+5V = Tx Amp Active / 0V = Rx Amp Active)
3	REV	Reverse Power Detection
4	GND	Ground
5	FWD	Forward Power Detection
A2	+VDC	Supply Voltage - Range Specified in Datasheet

DATA RATE VS. OUTPUT POWER	
OFDM MODULATION	POUT (W)
64QAM OFDM	10.0
16QAM OFDM	17.78
QPSK	19.95
BPSK	31.62

See our [application note](#) that describes how this data was taken and how you can apply it to your system








CONNECTOR PINOUT				
PIN	FUNCTION	HIGH	LOW	NOTES
1-4	+VDC	-	-	RETRUN FOR ALL SIGNAL AND CTRL PINS
5	SIG. GND	-	-	
6	GAIN CTRL	HIGH GAIN SETTING	LOW GAIN SETTING	
7	STATUS	NORMAL OPERATION	ERROR CONDITION	3.3V TTL LOGIC OUTPUT
8	TEMP	-	-	ANALOG TEMPERATURE SENSOR OUTPUT*
9-12	GND	-	-	+VDC SUPPLY RETURN
13-14	N/C	-	-	NOT USED - NO CONNECTION WITHIN AMP
15	Tx/Rx CTRL	SSPA IN TX MODE (LNA OFF, PA ON)	SSPA IN RX MODE (LNA ON, PA OFF)	3.3V TTL LOGIC INPUT (5V COMP) ONLY ACTIVE WHEN MANAL SWITCH IS ENABLED


NOTES:

1. VIEW FACING CONNECTOR INTERFACE (AMP SIDE)
2. P/N OF CONNECTOR ON AMPLIFIER: ITT MDM-15PSB
3. EQUATION TO CALCULATE TEMPERATURE AT PIN 8:
(VOLTAGE READ - 0.5V) x 100 = AMP TEMP IN DEG C

DRAWN	AHA	6/3/2014	Housing Outline 103		
DESIGNED	DMC	9/6/2013			
CHECKED	BG	6/17/2014	SIZE A	DWG/PART NO.	REV 0
ENG. APPROVED					
MFG. APPROVED			SCALE: NONE	CAGE CODE 67DZ3	SHEET 2 OF 3



MATE CABLE



MDM-15SSB

NOTES:

1. P/N OF MATING CONNECTOR REQUIRED: ITT MDM-15SSB OR EQUIVALENT
2. TRIAD CABLE P/N: C14061201
3. WIRE DIAMETER: 24 AWG

DRAWN	AHA	6/3/2014	Housing Outline 103		
DESIGNED	AHA	6/4/2014			
CHECKED	BG	6/17/2014	SIZE A	DWG/PART NO.	REV 0
ENG. APPROVED					
MFG. APPROVED			SCALE: NONE	CAGE CODE 67DZ3	SHEET 3 OF 3