

2 Way Power Divider SMA Connectors From 2 GHz to 8 GHz Rated at 30 Watts

Electrical Specifications*

Description	Min	Typ	Max	Units
Frequency Range	2		8	GHz
Impedance		50		Ohms
Insertion Loss		4		dB
Input Power			30	Watts
Input VSWR			1.4:1	
Output VSWR			1.4:1	
Isolation	20			dB
Phase Balance		± 4		Degrees
Flatness		0.3		dB

* Values at 25°C, sea level

Mechanical Specifications

Temperature

Operating Range -55 to +85 deg C

Size

Length 1.102 in 27.99 mm

Width 1.102 in 27.99 mm

Height 0.393 in 9.98 mm

Weight 0.04453 lbs 20.2 g

Connectors

Description	Input Connector	Outer Connectors
Type	SMA Female	SMA Female
Contact Material & Plating		Beryllium Copper, Gold
Body Material & Plating		Stainless Steel, Passivated

Compliance Certifications (visit www.FairviewMicrowave.com for current document)

RoHS Compliant Yes

Plotted and Other Data

Notes:

- Values at 25 °C, sea level




Features:

- Input Connector: SMA Female
- Output Connectors: SMA Female
- Frequency Range: 2 to 8 GHz
- Design: Wilkinson
- Number of Output Ports: 2
- Housing Material and Plating: Aluminum, Gray

Fairview Microwave
1130 Junction Dr. #100
Allen, TX 75013
Tel: 1-800-715-4396 / (972) 649-6678
Fax: (972) 649-6689
www.fairviewmicrowave.com
sales@fairviewmicrowave.com

Typical Performance Data




2 Way Power Divider SMA Connectors From 2 GHz to 8 GHz Rated at 30 Watts from Fairview Microwave is in-stock and available to ship same-day. All of our RF/microwave products are available off-the-shelf from our ISO 9001:2008 certified facilities in Allen, Texas. Fairview Microwave is RF on-demand.

For additional information on this product, please click the following link: [2 Way Power Divider SMA Connectors From 2 GHz to 8 GHz Rated at 30 Watts MP0208-2](http://www.fairviewmicrowave.com/2-way-power-divider-sma-8-ghz-20-watts-mp0208-2-p.aspx)

URL: <http://www.fairviewmicrowave.com/2-way-power-divider-sma-8-ghz-20-watts-mp0208-2-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume any liability arising out of the use of any part or documentation.



FAIRVIEW MICROWAVE INC.
ALLEN, TX 75013 WWW.FAIRVIEWMICROWAVE.COM

TITLE
2 Way Power Divider SMA Connectors From 2 GHz to 8 GHz Rated at 30 Watts

NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES [mm].

DWG NO		MP0208-2		CAGE CODE	
				3FKR5	
CAD FILE	011415	SHEET	SCALE	N/A	SIZE A
					5568