





产品型号 type	L	L1
SMA-KFD98	15.2	3.2
SMA-KFD389	16.0	4.0

Electrical Characteristics:

- Characteristic Impedance: $50\ \Omega$
- Frequency range: DC~18Ghz
- Contact resistance
Center conductor: $\leq 3.0\ m\Omega$
Out conductor: $\leq 2.0\ m\Omega$
- Insulation resistance: $\geq 5000M\Omega$
- Insulator withstanding: 1000V
- Durability: 500cycles

Application: MIL-C-39012/55D

Material&Finishing

- Center contact :
Female: beryllium, gold plated
- Body: brass, gold plated
- Insulators: PTFE

主要性能指标:

- 特性阻抗: $50\ \Omega$
- 频率范围: DC~18Ghz
- 接触电阻:
中心导体: $\leq 3.0\ m\Omega$
外导体: $\leq 2.0\ m\Omega$
- 绝缘电阻: $\geq 5000M\Omega$
- 介质耐压: 1000V
- 插拔次数: 500次

执行标准: MIL-C-39012/55D

材料和镀层

- 中心接触件:
插孔: 铍青铜, 镀金
- 壳体: 黄铜, 镀金
- 绝缘子: 聚四氟乙烯

		SCALE	
		2.5:1	
	NAME	DATE	
DRAWN			
CHECKED			
APPROVED			

SMA-KFD98
RF COAXIAL CONNECTOR

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE mm, TOLERANCES ARE
FRACTIONS DECIMALS ANGLES
.XX± .15 ±1°
.XX± .05
.XXX±

西安富士达科技股份有限公司
XI'AN FORSTAR S&T CO.,LTD.