

SMB Jack to BNC Female Adapter



TECHNICAL DATA SHEET

PE9136

SMB Jack to BNC Female Adapter

Configuration

Connector 1 SMB Jack Impedance 1 50 Ohms Connector Specification 1 MIL-C-39012 **BNC Female** Connector 2 Impedance 2 50 Ohms Adapter Design Standard Body Style Straight

Mechanical Specifications

Size

1.272 [32.31] Length, in [mm] 0.445 [11.3] Width/Dia., in [mm]

Connector 1

Type SMB Jack Inner Conductor Material and Plating Brass, Gold Inner Conductor Plating Specification 3μ-5μ in. minimum **Body Material and Plating** Brass, Nickel **Body Plating Specification** 70µ in. minimum Dielectric Type Teflon

Connector 2

BNC Female Type Inner Conductor Material and Plating Brass, Gold Inner Conductor Plating Specification 3μ-5μ in. minimum Body Material and Plating Brass, Nickel **Body Plating Specification** 70µ in. minimum Teflon

Dielectric Type

Compliance Certifications (visit www.Pasternack.com for current document) **RoHS Compliant**

Plotted and Other Data

Notes: Values at 25 °C, sea level

URL: http://www.pasternack.com/smb-jack-bnc-female-straight-adapter-pe9136-p.aspx

SMB Jack to BNC Female Adapter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

ISO 9001: 2008 Registered

PE9136 CAD Drawing

SMB Jack to BNC Female Adapter

