



Electrical Characteristics:

1. Characteristic Impedance: 50 Ω
2. Frequency range: DC~4Ghz
3. Contact resistance
Center conductor: ≤1.5 mΩ
Out conductor: ≤0.2 mΩ
4. Insulation resistance: ≥5000MΩ
5. Insulator withstanding: 1500V
6. Durability: 500cycles

主要性能指标:

1. 特性阻抗: 50 Ω
2. 频率范围: DC~4Ghz
3. 接触电阻:
中心导体: ≤1.5 mΩ
外导体: ≤0.2 mΩ
4. 绝缘电阻: ≥5000MΩ
5. 介质耐压: 1500V
6. 插拔次数: 500次

Application: MIL-C-39012/16E

执行标准: MIL-C-39012/16E

Material&Finishing

1. Center contact :
Female: phosphor bronze, gold plated
2. Bodies and other metal parts:
brass, nickel plated
3. Insulators: PTFE

材料和镀层

1. 中心接触件:
插孔: 锡磷青铜, 镀金
2. 壳体和其它金属零件:
黄铜, 镀镍
3. 绝缘子: 聚四氟乙烯

 	SCALE		BNC-KHD1 RF COAXIAL CONNECTOR	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE mm, TOLERANCES ARE FRACTIONS DECIMALS ANGLES .X± .15 ±1° .XX± .05 .XXX±
	1.5:1			
NAME	DATE			
DRAWN				
CHECKED				
APPROVED				

西安富士达科技股份有限公司
XI'AN FORSTAR S&T CO.,LTD.