



Electrical Characteristics:

1. Characteristic Impedance: 50 Ω
2. Frequency range: DC~7.5GHz
3. Contact resistance
Center conductor: ≤1.0 mΩ
Out conductor: ≤0.5 mΩ
4. Insulation resistance: ≥10000MΩ
5. Insulator withstanding: 4000V
6. Durability: 500cycles

主要性能指标:

1. 特性阻抗: 50 Ω
2. 频率范围: DC~7.5GHz
3. 接触电阻:
中心导体: ≤1.0 mΩ
外导体: ≤0.5 mΩ
4. 绝缘电阻: ≥10000MΩ
5. 介质耐压: 4000V
6. 插拔次数: 500次

Application: IEC 60169-4

执行标准: IEC 60169-4

Material & Finishing

1. Center contact :
Female: phosphor bronze, silver plated
2. Flange body: brass, nickel plated
Other metal parts: brass, silver plated
3. Insulators: PTFE

材料和镀层

1. 中心接触件:
插孔: 锡磷青铜, 镀银
2. 法兰壳体: 黄铜, 镀镍
其它金属零件: 黄铜, 镀银
3. 绝缘子: 聚四氟乙烯

 	SCALE	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE mm, TOLERANCES ARE FRACTIONS DECIMALS ANGLES .X± .15 ±1° .XX± .05 .XXX±
	1.5:1	
	NAME	L29-KF RF COAXIAL CONNECTOR
DRAWN	DATE	
CHECKED		
APPROVED		

西安富士达科技股份有限公司
XI'AN FORSTAR S&T CO.,LTD.