



50 Ohm BNC Female to 75 Ohm F Female Bulkhead Adapter

TECHNICAL DATA SHEET

PE91324

Configuration

Connector 1
Impedance 1
Connector 2
Impedance 2
Impedance 2
Adapter Design
Body Style
Mount Method

BNC Female
50 Ohms
Female
75 Ohms
Standard
Standard
Straight
Bulkhead

Electrical Specifications

Frequency Range DC to 1,000 MHz
Maximum VSWR 1.3:1

Mechanical Specifications

Size

Length, in [mm] 1.3 [33.02] Width/Dia., in [mm] 0.55 [13.97]

Connector 1

Type BNC Female
Inner Conductor Material and Plating Beryllium Copper, Gold
Body Material and Plating Brass, Nickel
Dielectric Type Teflon

Connector 2

Type F Female
Inner Conductor Material and Plating Beryllium Copper, Gold
Body Material and Plating Brass, Nickel
Dielectric Type Teflon

Environmental Specifications

Temperature

Operating Range -55 to +125 deg C

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant

REACH Compliant 6/18/2012

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 50 Ohm BNC Female to 75 Ohm F Female Bulkhead Adapter PE91324



© 2015 Pasternack Enterprises All Rights Reserved





50 Ohm BNC Female to 75 Ohm F Female Bulkhead Adapter

TECHNICAL DATA SHEET

PE91324

Plotted and Other Data

Notes:

• Values at +25 °C, sea level

50 Ohm BNC Female to 75 Ohm F Female Bulkhead Adapter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 50 Ohm BNC Female to 75 Ohm F Female Bulkhead Adapter PE91324

URL: http://www.pasternack.com/bnc-female-f-female-straight-adapter-pe91324-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.



