



# TNC Male Right Angle Connector Crimp/Solder Attachment For PE-C200, LMR-200

### TECHNICAL DATA SHEET

PE44846

Configuration

Connector TNC Male

Connector Interface Type PE-C200, LMR-200
Attachment Method (Shield/Contact) Crimp/Solder
Body Style Right Angle

**Electrical Specifications** 

Frequency Range DC to 11 GHz
Impedance 50 Ohms
Dielectric Withstanding Voltage 500 Vrms

Frequency 1

Frequency DC to 6 GHz VSWR 1.35:1

**Mechanical Specifications** 

**Temperature** 

Operating Range -65 to +165 deg C

Size

 Length
 1.44 in [36.58 mm]

 Width/Dia.
 1.04 in [26.42 mm]

 Height
 0.57 in [14.48 mm]

Connector

Type TNC Male
Contact Material and Plating Brass, Gold
Coupling Nut Material and Plating Brass, Nickel
Body Material and Plating Brass, Nickel
Dielectric Type PTFE

Compliance Certifications (visit www.Pasternack.com for current document)

**RoHS Compliant** 

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: TNC Male Right Angle Connector Crimp/Solder Attachment For PE-C200, LMR-200 PE44846







## TNC Male Right Angle Connector Crimp/Solder Attachment For PE-C200, LMR-200

#### TECHNICAL DATA SHEET

PE44846

#### **Plotted and Other Data**

Notes:

• Values at +25 °C, sea level

TNC Male Right Angle Connector Crimp/Solder Attachment For PE-C200, LMR-200 from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: TNC Male Right Angle Connector Crimp/Solder Attachment For PE-C200, LMR-200 PE44846

URL: http://www.pasternack.com/tnc-male-standard-pe-c200-lmr-200-connector-pe44846-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.



