

DESCRIPTION

PMI MODEL PDVAT-0518-60-8-96-OPT0108 IS A 1.0 TO 8.0 GHz VARIABLE ATTENUATOR/MODULATOR WITH 8 BIT BINARY TTL CONTROL OR OPTIONAL ANALOG VOLTAGE CONTROL.

SPECIFICATIONS

- FREQUENCY RANGE: 1.0 TO 8.0 GHz
- INSERTION LOSS: 4.0 dB MAXIMUM
- ATTENUATION FLATNESS:
 - @ 10 dB = ± 0.9 dB
 - @ 20 dB = ± 1.5 dB
 - @ 40 dB = ± 3.0 dB
 - @ 60 dB = ± 5.0 dB
- ATTENUATION ACCURACY:
 - 0-30 dB = ± 1.0 dB
 - 30-50 dB = ± 1.3 dB
 - 50-60 dB = ± 1.5 dB
- MONOTONICITY: GUARANTEED
- TEMPERATURE VARIATION:
 - ± 2.5 dB -10 to 85°C Typ
 - ± 3.5 dB -40 to 95°C Typ
- SWITCHING TIME: 1.5 micro sec MAXIMUM
- SMALL SIGNAL BANDWIDTH: 150 kHz Typ (6dB with ± 3 dB sinewave)
- LARGE SIGNAL BANDWIDTH: 75 kHz Typ (30dB with ± 30 dB sinewave)
- RETURN LOSS: -12 dB TYP -8.5 dB MAX
- POWER RATING: +20 dBm (see note 1)
- DIGITAL CONTROL: 8 BIT TTL
- 0.25 dB MINIMUM ATTENUATION STEP
- ANALOG CONTROL option: 0-6V ANALOG VOLTAGE, 10dB/VOLT
- POWER SUPPLY: +12V TO +15V @ 150 mA MAXIMUM
- CONNECTORS
 - RF INPUT/OUTPUT: FIELD REPLACEABLE SMA (FEMALE)
 - POWER AND CONTROLS: 15 PIN MICRO-D FEMALE
- MATING CONNECTOR (MALE) FURNISHED
- FINISH: PAINTED BLUE
- SIZE: 2.00" x 1.80" x 0.50"

NOTE 1: REDUCED POWER PERFORMANCE AT LOW FREQUENCIES

ALL DIMENSIONS ARE IN INCHES

TOLERANCES:

X.XX ± 0.020
X.XXX ± 0.010

ENVIRONMENTAL RATINGS



- TEMPERATURE: -40°C TO + 85°C (OPERATING)
-65°C TO +125°C (STORAGE)
- HUMIDITY: MIL-STD-202F, METHOD 103B COND. B
- SHOCK: MIL-STD-202F, METHOD 213B COND. B
- VIBRATION: MIL-STD-202F, METHOD 204D COND. B
- ALTITUDE: MIL-STD-202F, METHOD 105C COND. B
- TEMPERATURE CYCLE: MIL-STD-202F, METHOD 107D COND. A

NOTE: SPECIFICATIONS WILL VARY OVER OPERATING TEMPERATURE
NOTE: THE ABOVE SPECIFICATIONS ARE SUBJECT TO CHANGE OR REVISION

PIN NO:	J3 PIN FUNCTIONS
1	2dB
2	1dB
3	0.5dB
4	0.25dB (LSB)
5	GND
6	Not Used
7	Not Used
8	GND
9	Not Used
10	Not Used
11	+VDC
12	32dB (MSB)
13	16dB
14	8dB
15	4dB

REVISIONS			
ZONE	REV.	DESCRIPTION	DATE
	—	PRELIMINARY	7/17/15
			JS

MECHANICAL OUTLINE



PMI CONFIDENTIAL AND PROPRIETARY

PLANAR MONOLITHICS INDUSTRIES, INC.

7311-F GROVE ROAD
FREDERICK, MARYLAND 21704 USA
TEL: 301-662-5019 FAX: 301-662-1731
WEBSITE: www.pmi-rf.com
E-MAIL: sales@pmi-rf.com
ISO 9001 CERTIFIED



APPROVALS		DATE		TITLE	
DRAWN JS		7/17/15		PRODUCT FEATURE	
CHECKED				PDVAT-0518-60-8-96-OPT0108	
ISSUED				PRELIMINARY	
SCALE N:S		FSCM NO. A 05XQ0		DWG NO.	
				SHEET 1 OF 1	