


REVISIONS				
ZONE	REV	DESCRIPTION	Date	APPROVED



SPECIFICATIONS

Frequency Range: 14–14.5 GHz
 Insertion Loss: 3.4dB Max.
 Isolation: 11dB Min.
 Amplitude balance: ± 1.8 dB
 Phase balance: ± 12 Deg.
 VSWR: 2.00:1 Max.
 Power: 10W Max.

MCLI

MICROWAVE COMMUNICATIONS LABORATORIES INC.
 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710
 TEL: (727) 344-6254 FAX: (727) 381-6116
<http://WWW.MCLI.COM>

SCALE: N/A
 SHEET: N/A

UNLESS OTHERWISE SPECIFIED:
 TOLERANCES
 IN (INCHES) OR (mm) (MILLIMETERS)
 FRACTIONS: $\pm 1/64$
 DECIMALS: $\pm 0.01 \pm 0.005$
 ANGLE: $\pm 1/2^\circ$

DRAWING TITLE:

12-WAY POWER DIVIDER

PART NO.

PS12-26


DRAWN: Paiboon Luekhamhan

DATE: 03-16-2012

APPROVED: T. Nguyen

DATE: 03-16-2012

PROPRIETARY NOTICE:
 THE INFORMATION IN THIS DRAWING IS PROPRIETARY
 AND SHALL NOT BE USED OR DISCLOSED WITHOUT WRITTEN
 PERMISSION FROM MICROWAVE COMMUNICATIONS
 LABORATORIES INC. (MCLI)



CAGE CODE:

0D2L5

SIZE:

A

REV:

N/A

DWG NO.

86032

DO NOT SCALE THE DRAWING