


REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED



SPECIFICATIONS

Frequency Range: 0.8–2.3 GHz
Coupling: 10 ± 1.25 dB
Frequency Sensitivity: ± 0.5 dB
Insertion Loss: 1.0 dB Max.
Directivity: 20 dB Min.
VSWR: 1.30:1 Max.
Power Incident, Reflected: 50W, 5W, 1kW Peak

MATERIAL: 		MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM		SCALE: N/A
		UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR [mm] (MILLIMETERS) FRACTIONS: $\pm 1/64$ DECIMALS: $\pm 0.01 \pm 0.005$ ANGLE: $\pm 1/2^\circ$		SHEET: N/A
DRAWING TITLE: DIRECTIONAL COUPLER		PART NO.: C37-10/NMI		
DRAWN: Paiboon Luekhamhan	DATE: 01-29-2008	CAGE CODE: OD2L5	SIZE: A REV: A DO NOT SCALE THE DRAWING	DWG NO.: 83049
APPROVED: T. Nguyen		DATE: 01-29-2008		