

Ultra Miniature SMD HCMOS TCXO



Model: FOX351 Series

RoHS Compliant / Pb Free

Rev. 2/23/2013

Page 1 of 1

http://www.foxonline.com/need_a_sample.htm

Need a
Sample®

• PART NUMBER SELECTION

Part Number	Model Number	Supply Voltage (V _{DD})
835-Frequency-xxxxx	FOX351C	3.3V±5%
835A-Frequency-xxxxx	FOX351D	2.8V±5%
835B-Frequency-xxxxx	FOX351G	2.5V±5%

• ELECTRICAL CHARACTERISTICS

PARAMETERS	MAX (unless otherwise noted)
Frequency Range (MHz)	4.000 ~ 54.000
Temperature Range	
Operating (T _{OPR})	-30°C ~ +75°C
Storage (T _{STG})	-40°C ~ +125°C
Supply Voltage (V _{DD})	+2.5V ~ +3.3 V _{DC} ±5%
Input Current (I _{DD})	See table below
Standby Current	10uA
Initial Frequency Tolerance @ 25°C (after 2 reflows)	±1.5 PPM
Frequency Stability	
Over Temp Range	±2.5 PPM
Over Supply Voltage Change (V _{DD} ±5%)	±0.2 PPM
Over Load Range (15pF ±10%)	±0.2 PPM
Rise Time (10% ~ 90% V _{DD}) (T _r)	5nS
Fall Time (90% ~ 10% V _{DD}) (T _f)	5nS
Symmetry (50% V _{DD})	45% ~ 55%
Output Voltage (V _{OL})	10% V _{DD}
(V _{OH})	90% V _{DD} MIN
Output Load (C _L)	15pF
Aging per year	±1.0PPM
Startup Time (T _s)	10mS
Disable Time	250nS
Enable Time	10mS
Phase Noise @ 10kHz offset	-145dBc/Hz Typical
Reflow Soldering Temp	260°C / 10 Seconds
Moisture Sensitivity Level (MSL)	1
Termination Finish	Au

• INPUT CURRENT (I_{DD}) (mA Max)


	4 ~ 10MHz	10+ ~ 20MHz	20+ ~ 30MHz	30+ ~ 40MHz	40+ ~ 54MHz
2.5V	3.1	3.7	4.2	4.6	5.5
2.8V	3.4	4.1	4.7	5.2	6.0
3.3V	4.0	4.8	5.5	6.0	7.0

• STANDARD FREQUENCIES¹

5.000MHz	10.000MHz	12.000MHz
16.000MHz	20.000MHz	24.000MHz
32.000MHz	40.000MHz	44.000MHz

¹ Does not imply a stocked part.

² An internal pullup resistor from pin 1 to pin 4 allows active output if pin 1 is left open.
Dimensional drawing is for reference to critical specifications defined by size measurements.
Certain non-critical visual attributes, such as side castellations, reference pin shape etc. may vary. All specifications are subject to change without notice



• ENABLE / DISABLE FUNCTION

(Pin 1)	OUTPUT (Pin 3)
OPEN ²	ACTIVE
'1' Level V _{IH} ≥ 70% V _{DD}	ACTIVE
'0' Level V _{IL} ≤ 30% V _{DD}	High Z