



75 Ohm Mini SMB Jack Connector Solder Attachment
Thru Hole PCB, .200 inch x .055 inch Hole Spacing

TECHNICAL DATA SHEET

PE4997

75 Ohm Mini SMB Jack Connector Solder Attachment Thru Hole PCB, .200 inch x .055 inch Hole Spacing

Configuration

Connector	Mini SMB Jack
Connector Interface Type	Thru Hole
Cable Attachment Method (Shield/Contact)	Solder
Body Style	Straight

Electrical Specifications

Impedance, Ohms	75
-----------------	----

Mechanical Specifications

Size

Length, in [mm]	0.448 [11.38]
Width/Dia., in [mm]	0.25 [6]
Height, in [mm]	0.25 [6.35]
Weight, lbs [g]	0.003 [1.36]

Connector

Type	Mini SMB Jack
Contact Material and Plating	Brass, Gold
Contact Plating Specification	30µ in. minimum
Body Material and Plating	Brass, Gold
Body Plating Specification	3µ in. minimum
Dielectric Type	Teflon

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant	Yes
----------------	-----

Plotted and Other Data

Notes:	Values at 25 °C, sea level
--------	----------------------------

75 Ohm Mini SMB Jack Connector Solder Attachment Thru Hole PCB, .200 inch x .055 inch Hole Spacing from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [75 Ohm Mini SMB Jack Connector Solder Attachment Thru Hole PCB, .200 inch x .055 inch Hole Spacing PE4997](http://www.pasternack.com/mini-smb-jack-standard-thru-hole-pcb-connector-pe4997-p.aspx)

URL: <http://www.pasternack.com/mini-smb-jack-standard-thru-hole-pcb-connector-pe4997-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

75 Ohm Mini SMB Jack Connector Solder Attachment Thru
Hole PCB, .200 inch x .055 inch Hole Spacing



PE4997

PE PASTERNAK®
Pasternack Enterprises, Inc.
P.O. Box 16759 | Irvine | CA | 92623
Phone: (949) 261-1920 | **Fax:** (949) 261-7451
Website: www.pasternack.com | **E-Mail:** sales@pasternack.com

FSCM NO. 53919

SIZE A

127