



50 Ohm SMA Circulator Operating From 2 GHz to
4 GHz And 10 Watts With 18 dB Isolation

TECHNICAL DATA SHEET

PE8401

Configuration

Connector 1	SMA Female
Connector 2	SMA Female
Connector 3	SMA Female
Frequency Range	2 GHz to 4 GHz
Design	Circulator

Electrical Specifications (Values at 25°C, sea level)

Description	Minimum	Typical	Maximum	Units
Frequency Range	2		4	GHz
Impedance		50		Ohms
Insertion Loss			0.6	dB
Forward Power			10	Watts
Reverse Power			10	Watts
Input VSWR			1.3:1	
Isolation	18			dB

Mechanical Specifications

Size	
Length	2.35 in [59.69 mm]
Width	1.975 in [50.17 mm]
Height	0.6 in [15.24 mm]

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant	Yes
REACH Compliant	06/18/2010

Plotted and Other Data

- Notes:
- Values at 25 °C, sea level

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [50 Ohm SMA Circulator Operating From 2 GHz to 4 GHz And 10 Watts With 18 dB Isolation PE8401](#)

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.




50 Ohm SMA Circulator Operating From 2 GHz to 4 GHz And 10 Watts With 18 dB Isolation

TECHNICAL DATA SHEET

PE8401

Outline Drawing



50 Ohm SMA Circulator Operating From 2 GHz to 4 GHz And 10 Watts With 18 dB Isolation from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [50 Ohm SMA Circulator Operating From 2 GHz to 4 GHz And 10 Watts With 18 dB Isolation PE8401](http://www.pasternack.com/50-ohm-sma-circulator-2000-mhz-4000-mhz-10-watts-18-db-pe8401-p.aspx)

URL: <http://www.pasternack.com/50-ohm-sma-circulator-2000-mhz-4000-mhz-10-watts-18-db-pe8401-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.