



Model: SR-F000-2S

Description:	SP2T, Reflective, High Power PIN-Switch
Operating Frequency:	8 - 12 GHz
Insertion Loss:	1.5 dB Max
Isolation:	50 dB Min
VSWR (Path "ON"):	1.5:1 Max
Rise/Fall time (10% to 90% RF, 90% to 10% RF):	25 ns Max
On/Off time (50% TTL to 90% RF, 50%TTL to 10% RF):	75 ns Max
Operating Power:	CW & AVG..... +37dBm Max / Hot Switching
	Peak: +47dBm @ 1 μ S PW Max
Control Input Characteristics:	TTL /Unit-Load, 1-Control / Flouting-High
Control Logic:	Logic "0" J0-J1 Path "ON"
	Logic "1" J0-J2 Path "ON"
Power Supplies:	+5($\pm$ 0.25)V @ 80mA Max
	-15($\pm$ 0.5)V @ 80mA Max
Connectors (RF):	SMA (f), Removable
Connectors (Supplies/Control)	Solder Pins
Impedance:	50 Ohms Nominal
Weight:	0.9 oz [25.5 g]
Quality:	Best-Commercial-Grade

Environmental Ratings:

Temperature:	{Operating: -55°C to +95°C} & {Storage: -60°C to +110°C}
Humidity:	MIL-STD-202F, Method 103B, Cond. B (96 hours at 95% R.H.)
Shock:	MIL-STD-202F, Method 213B, Cond. B (75G, 6mSec)
Vibration:	MIL-STD-202F, Method 204D, Cond. B (.06" double amplitude, or 15G)
Altitude:	MIL-STD-202F, Method 105C, Cond. B (50,000 Feet)
Temp. Shock:	MIL-STD-202F, Method 107D, Cond. A (5 cycles)

Available Options:

(Units with listed options here may be subject to some specification tradeoffs from the standard, consult factory)

■ **RF Connectors**

- B1 [J1 & J2 Ports with SMA(M)]
- B2 [All Ports with SMA(M)]
- B3 [COM (J0) Port with SMA(M)]

■ **Control Impedance**

- D1 [50 Ω , Internally Terminated]

■ **Control Function**

- F1 [Inverse Logic, ("1" = For "J1" Port "ON")]



Universal Microwave Components Corp.

5702-D General Washington Drive Alexandria, VA 22312 <> Web: www.umcc111.com

E-mail: sales@umcc111.com <> Tel: (703) 642-6332 <> Fax: (703) 642-2568

Model: SR-F000-2S

Outline

