


REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED



SPECIFICATIONS

Frequency Range: 200–500 MHz
 Insertion Loss: 0.35dB Max.
 Isolation: 20dB Min.
 Power Rating: 500 W CW
 Amplitude Balance: ± 0.10 dB Max.
 VSWR: 1.30:1 Max.
 Phase Balance: ± 5 Deg. Max.

MATERIAL: UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR [mm] (MILLIMETERS) FRACTIONS: $\pm 1/64$ DECIMALS: $\pm 0.01 \pm 0.05$ ANGLE: $\pm 1/2^\circ$		MCLI MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM		SCALE: N/A
		DRAWING TITLE: 2-WAY POWER DIVIDER		SHEET: N/A
DRAWN: Paiboon Luekhamhan DATE: 12-21-2005		PART NO.: PLH2-500/NF		
APPROVED: T. Nguyen DATE: 12-21-2005		CAGE CODE: OD2L5	SIZE: N/A DO NOT SCALE THE DRAWING	REV: N/A DWG NO.: 82460