

17 Coaxial Fixed Termination

Vector Telecom supplies high quality Coaxial Terminations up to 18 GHz. Our Free Standing Convection Cooled Terminations offer great flexibility for all your engineering applications. Please call us with your requirements and discuss your needs with one of our sales engineers.



【Specifications】

Model No*	Avg Power (W)	Peak Power (kW)	Freq Range (GHz)	VSWR	Coax Connector Type	Impedance (Ω)
VT124CL2S...	2	0.25	DC-12.4	1.10-1.25	SMA	50
VT040CL2S...	2	0.25	DC-4	≤ 1.20	SMA	50
VT400CL2S...	2	0.25	DC-40	1.10-1.40	SMA	50
VT180CL2S1...	2	0.25	DC-18	1.10-1.30	SMA	50
VT180CL2S2...	2	0.25	DC-18	1.05-1.30	SMA	50
VT180CL2S3...	2	0.5	DC-18	≤ 1.25	SMA	50
VT400CL5S...	5	0.5	DC-40	≤ 1.40	SMA	50
VT180CL10S...	10	0.5	DC-18	≤ 1.45	SMA	50
VT060CL2N...	2	0.5	DC-6	1.10-1.25	N,SMA,BNC,TNC,7/16	50
VT180CL2N...	2	0.5	DC-18	1.10-1.30	N,BNC,SMA,TNC,7/16	50
VT030CL2...	2	1	DC-3	≤ 1.10	7/16 (M)	50
VT080CL2N...	2	0.5	DC-8	1.10-1.25	N(M)	50
VT060CL5N1...	5	0.5	DC-6	1.10-1.30	N,BNC,SMA,TNC,7/16	50
VT060CL5N2...	5	1	DC-6	1.10-1.25	N(M)	50
VT180CL5N1...	5	0.5	DC-18	1.10-1.30	N	50
VT180CL5N2...	5	0.5	DC-18	1.10-1.30	N,BNC,SMA,TNC	50
VT060CL10N...	10	1	DC-6	1.10-1.30	N,BNC,SMA,TNC,7/16	50
VT100CL10N...	10	1	DC-10	1.10-1.45	N	50
VT180CL10N1...	10	1	DC-18	1.10-1.40	N,SMA,BNC,TNC	50
VT180CL10N2...	10	1	DC-18	1.10-1.30	N	50
VT060CL25N...	25	1	DC-6	1.10-1.25	SMA,N,7/16,TNC,BNC	50
VT100CL25N...	25	1	DC-10	1.10-1.45	N	50
VT180CL25N...	25	1	DC-18	1.15-1.35	N,SMA,TNC	50
VT060CL30N...	30	10	DC-6	1.10-1.30	N,SMA,7/16,TNC,BNC	50
VT100CL30N...	30	1	DC-10	1.10-1.45	N	50
VT040CL50N1...	50	10	DC-4	1.05-1.20	N,SMA,7/16,TNC	50

Section 2
Coaxial
Components

17
Coaxial
Fixed
Termination



Vector Telecom Pty Ltd

Website: www.vectortele.com

Email: sales@vectortele.com



Vector Telecom

Section 2
Coaxial
Components

17

Coaxial
Fixed
Termination



Vector Telecom Pty Ltd

Website: www.vectortele.com

Email: sales@vectortele.com

Model No*	Avg Power (W)	Peak Power (kW)	Freq Range (GHz)	VSWR	Coax Connector Type	Impedance (Ω)
VT060CL50N...	50	1	DC-6	1.10-1.25	N,BNC,7/16,TNC	50
VT100CL50N...	50	1	DC-10	1.10-1.45	N	50
VT180CL50N1...	50	1	DC-18	1.10-1.45	N,SMA	50
VT180CL50N2...	50	5	DC-18	1.10-1.55	N,7/16,SMA	50
VT040CL80N...	80	10	DC-4	1.05-1.25	N,7/16,TNC	50
VT180CL80N1...	80	1	DC-18	1.15-1.45	N	50
VT180CL80N2...	80	5	DC-18	1.15-1.55	N	50
VT040CL100N1...	100	10	DC-4	1.10-1.25	N,7/16	50
VT180CL100N1...	100	5	DC-18	1.10-1.25	N	50
VT180CL100N2...	100	5	DC-18	1.10-1.55	N	50
VT040CL150N...	150	10	DC-4	1.15-1.30	N,7/16	50
VT180CL150N1...	150	10	DC-18	1.15-1.50	N	50
VT180CL150N2...	150	5	DC-18	1.15-1.55	N	50
VT040CL200N...	200	10	DC-4	1.15-1.30	N,7/16	50
VT100CL200N...	200	5	DC-10	1.10-1.35	N,7/16	50
VT040CL250N...	250	10	DC-4	1.15-1.35	N,7/16	50
VT100CL25N2...	25	5	DC-10	1.10-1.35	N,7/16	50
VT040CL300N1...	300	10	DC-4	1.15-1.40	N, 7/16	50
VT100CL300N...	300	5	DC-10	1.10-1.35	N,7/16	50
VT040CL400N...	400	10	DC-4	1.15-1.45	N,7/16	50
VT100CL400N...	400	10	DC-10	1.10-1.50	N,7/16	50
VT040CL500N1...	500	10	DC-4	1.15-1.40	N,7/16	50
VT040CL500N2...	500	5	DC-4	1.15-1.55	N,7/16	50
VT040CL800N...	800	10	DC-4	1.20-1.45	N,7/16	50
VT040CL1000N...	1000	10	DC-4	≤1.40	N,7/16,L27	50
VT040CL1500N...	1500	10	DC-4	≤1.40	N,7/16,L27	50
VT040CL2000N...	2000	10	DC-4	≤1.40	N,7/16,L27	50
VT020CL1000N...	1000	50	DC-2	≤1.30	N,7/16,L27	50
VT020CL2000N...	2000	50	DC-2	≤1.30	N,7/16,L27	50
VT020CL3000N...	3000	50	DC-2	≤1.30	L27, 7/16,L36	50
VT010CL5000N...	5000	100	DC-1	≤1.40	L27, 7/16,L52	50
VT030CL1N...	1	0.5	DC-3	≤1.20	N, NBC	75
VT030CL2N...	2	0.5	DC-3	≤1.20	N, NBC	75
VT030CL5N...	5	0.5	DC-3	≤1.20	N, NBC	75
VT030CL50N...	50	5	DC-3	≤1.05	N	50
VT030CL150N...	150	5	DC-3	≤1.05	N	50



Vector Telecom

Section 2
Coaxial
Components



Coaxial
Fixed
Termination



Vector Telecom Pty Ltd

Website: www.vectortele.com

Email: sales@vectortele.com

Model No*	Avg Power (W)	Peak Power (kW)	Freq Range (GHz)	VSWR	Coax Connector Type	Impedance (Ω)
VT085CL30N...	30	5	DC-8.5	≤1.30	N,SMA	50
VT180CL50N3...	50	5	DC-18	≤1.55	N,SMA	50
VT180CL75N...	75	5	DC-18	≤1.55	N,SMA	50
VT180CL150N3...	150	5	DC-18	≤1.55	N	50
VT040CL50N2...	50	10	DC-4	≤1.30	N	50
VT040CL100N2...	100	10	DC-4	≤1.30	N	50
VT040CL300N2...	300	10	DC-4	≤1.40	N	50
VT180CL50N4...	50	5	DC-18	≤1.55	N	50
VT180CL100N3...	100	5	DC-18	≤1.55	N	50
VT180CL200N...	200	5	DC-18	≤1.55	N	50
VT0820CL300N...	300	5	0.8-2	≤1.20	N	50
VT0820CL350N...	350	5	0.8-2	≤1.20	N	50
VT1214CL300N...	300	12	1.2-1.4	≤1.20	N	50
VT040CL25N...	25	1	DC-4	≤1.20	N	50
VT040CL30N...	30	1	DC-4	≤1.20	N	50
VT040CL50N3...	50	1	DC-4	≤1.20	N	50
VT040CL80N...	80	1	DC-4	≤1.20	N	50
VT040CL100N3...	100	5	DC-4	≤1.20	N	50

*Indicates Model Number. See Ordering Information for complete part number.

【Ordering Information】

