

Plug-In

Frequency Mixer

Level 10 (LO Power +10 dBm) 0.15 to 400 MHz

TUF-3LH+



CASE STYLE: B02
PRICE: \$12.20 ea. QTY (10)

Maximum Ratings

Operating Temperature	-55°C to 100°C
Storage Temperature	-55°C to 100°C
RF Power	50mW
IF Current	40mA
Permanent damage may occur if any of these limits are exceeded.	

Pin Connections

LO	4
RF	1
IF	2
GROUND	3
CASE GROUND	3

Features

- low conversion loss, 4.8 dB typ.
- high isolation, 51 dB typ. L-R, 45 dB typ. L-I
- rugged welded construction


Applications

- HF/VHF
- defense & federal communications

+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

Outline Drawing



Outline Dimensions (inch/mm)

A	B	C	D	E	F
.480	.500	.240	.255	.210	.230
12.19	12.70	6.10	6.48	5.33	5.84
G	H	J	K	L	wt
.16	.100	.14	.20	.020	grams
4.06	2.54	3.56	5.08	0.51	1.9

Electrical Specifications

FREQUENCY (MHz)		CONVERSION LOSS (dB)				LO-RF ISOLATION (dB)						LO-IF ISOLATION (dB)					
LO/RF	IF	Mid-Band		Total Range		L	M	U				L	M	U			
f_L - f_U		$\bar{X}$	σ	Max.	Max.	Typ.	Min.	Typ.	Min.	Typ.	Min.	Typ.	Min.	Typ.	Min.	Typ.	Min.
0.15-400	DC-400	4.8	0.37	7.0	8.0	67	50	51	30	40	25	67	40	45	25	34	20

1 dB COMP.: +5 dBm typ.

L = low range [f_L to $10 f_L$]

M = mid range [$10 f_L$ to $f_U/2$]


U = upper range [$f_U/2$ to f_U]

m = mid band [$2f_L$ to $f_U/2$]

Typical Performance Data

Frequency (MHz)		Conversion Loss (dB)	Isolation L-R (dB)	Isolation L-I (dB)	VSWR RF Port (:1)	VSWR LO Port (:1)
RF	LO	LO +10dBm	LO +10dBm	LO +10dBm	LO +10dBm	LO +10dBm
0.15	30.15	4.98	69.38	85.98	1.21	2.67
0.30	30.30	4.90	69.38	85.28	1.15	2.64
0.50	30.50	4.83	69.26	86.26	1.10	2.57
1.00	31.00	4.74	69.26	83.06	1.06	2.52
1.50	31.50	4.69	69.08	80.98	1.03	2.36
2.00	32.00	4.66	68.95	78.75	1.02	2.40
5.00	35.00	4.62	68.20	71.20	1.01	2.33
10.00	40.00	4.59	66.47	65.07	1.02	2.31
20.00	50.00	4.68	63.23	59.53	1.02	2.25
50.00	80.00	4.66	56.07	50.61	1.02	2.25
57.27	87.27	4.67	54.97	49.44	1.01	2.29
100.00	70.00	4.67	50.23	45.42	1.01	2.25
114.39	84.39	4.68	48.98	45.06	1.01	2.28
171.51	14.15	4.80	45.17	42.49	1.01	2.33
200.00	170.00	4.81	42.29	40.27	1.01	2.44
228.64	198.64	4.90	41.00	37.35	1.04	2.39
285.76	255.76	5.11	48.00	34.00	1.09	2.41
342.88	312.88	5.17	39.79	33.43	1.20	2.58
385.72	356.72	5.29	34.24	31.62	1.23	2.76
400.00	370.00	5.48	34.34	30.09	1.27	2.78

Electrical Schematic



Mini-Circuits®
ISO 9001 ISO 14001 AS 9100 CERTIFIED

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 The Design Engineers Search Engine Provides ACTUAL Data Instantly at minicircuits.com

IF/RF MICROWAVE COMPONENTS

For detailed performance specs & shopping online see web site

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.

REV. A
M98898
TUF-3LH+
DJ/TD/CP/AM
130502
Page 1 of 2

