



Model: PS-1000-6S

Description:..... 6-Way Power Divider

Operating Frequency:..... 30–800 MHz

Insertion Loss / Amplitude Balance / Phase Balance:

Frequency	Insertion Loss	Ampl. Bal	Phase Bal.
30 - 500 MHz	1.3dB Max	±0.2dB Max	±3°Max
500 - 800 MHz	1.5dB Max	±0.5 dB Max	±4°Max

Isolation: 25 dB Min

VSWR: Σ Port..... 1.6:1 Max

..... Output Ports 1.5:1 Max

Power Handling (@ SUM-Port): Load VSWR= ∞ 2W AVG/CW Max

..... Load VSWR <2:1..... 8W AVG/CW Max

Connectors: SMA (f)

Impedance: 50 Ohms Nominal

Quality: Best-Commercial-Grade

Environmental Ratings:

Temperature:..... {Operating: -55°C to +95°C} & {Storage: -60°C to +110°C}

Humidity: MIL-STD-202F, Method 103B Cond. B (96 hours at 95% R.H.)

Shock: MIL-STD-202F, Method 213B, Cond. B (75G, 6mSec)

Vibration: MIL-STD-202F, Method 204D, Cond. B (.06" double amplitude, or 15G)

Altitude: MIL-STD-202F, Method 105C, Cond. B (50,000 Feet)

Temp. Shock: MIL-STD-202F, Method 107D, Cond. A (5 cycles)

Outline

(Tolerances: ±0.015" [0.38mm] <> Weight = 4.2oz [119g])

