


REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED



Specifications:

Frequency Range: 6–18 GHz
 Attenuation: 60dB
 Insertion Loss: 0.9 Max.
 VSWR: 1.50:1
 RF Power: 7W Average, 3kW Peak

Environmental:

Temperature range: –55°C to +110°C
 Shock: 15 G's, 11mS, 1/2 sine
 Vibration: 3 G's overall
 Altitude: 40,000 ft. Survival 25,000ft Operating

MATERIAL: 		MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM		SCALE: N/A
		UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR [mm] (MILLIMETERS) FRACTIONS: $\pm 1/64$ DECIMALS: ± 0.01 ± 0.005 ANGLE: $\pm 1/2^\circ$		SHEET: N/A
DRAWING TITLE: CONTINUOUSLY VARIABLE ATTENUATOR WITH DIAL		PART NO. CVA23-60/D		
DRAWN: Paiboon Luekhamhan	DATE: 02-08-2011	CAGE CODE: 0D2L5	SIZE: A	REV: N/A
APPROVED: T. Nguyen	DATE: 02-08-2011	DO NOT SCALE THE DRAWING		DWG NO. 85375