





安装开孔
mounting hole



Electrical Characteristics:

1. Characteristic Impedance: 50 Ω
2. Frequency range: DC~3Ghz
3. Contact resistance
Center conductor: $\leq 5.0 \text{ m}\Omega$
Out conductor: $\leq 2.5 \text{ m}\Omega$
4. Insulation resistance: $\geq 1000 \text{ M}\Omega$
5. Insulator withstanding: 750V
6. Durability: 500cycles

主要性能指标:

1. 特性阻抗: 50 Ω
2. 频率范围: DC~3Ghz
3. 接触电阻:
中心导体: $\leq 5.0 \text{ m}\Omega$
外导体: $\leq 2.5 \text{ m}\Omega$
4. 绝缘电阻: $\geq 1000 \text{ M}\Omega$
5. 介质耐压: 750V
6. 插拔次数: 500次

Application: IEC 601169-36

执行标准: IEC 601169-36

Material&Finishing

1. Center contact :
Female: beryllium copper, gold plated
2. Body: brass, gold plated
3. Insulators: PTFE

材料和镀层

1. 中心接触件:
插孔: 铍青铜, 镀金
2. 壳体: 黄铜, 镀金
3. 绝缘子: 聚四氟乙烯

		SCALE	
		4:1	
	NAME	DATE	
DRAWN			
CHECKED			
APPROVED			

MCX-KPD1
RF COAXIAL CONNECTOR

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE mm, TOLERANCES ARE
FRACTIONS DECIMALS ANGLES
.X $\pm$.15 $\pm 1^\circ$
.XX $\pm$.05
.XXX $\pm$

西安富士达科技股份有限公司
XI'AN FORSTAR S&T CO.,LTD.