


REVISIONS				
ZONE	REV	DESCRIPTION	Date	APPROVED



SPECIFICATIONS:

Frequency Range: 15–18.2 GHz

Isolation: 23dB Min.

Insertion loss: 0.4dB Max.

VSWR: 1.15:1 Max.

Operating Temperature: –54°C to +85°C

Forward Power: 2 Watts

Reverse Power: 0.25 Watt

MATERIAL: 		 MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM		SCALE: N/A	
				SHEET: N/A	
DRAWN: Paiboon Luekhamhan		DATE: 02-16-2011		DRAWING TITLE: COAXIAL ISOLATOR	
APPROVED: T. Nguyen		DATE: 02-16-2011		PART NO.: IS-159	
PROPRIETARY NOTICE: THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICROWAVE COMMUNICATIONS LABORATORIES INC. (MCLI)		THIRD ANGLE PROJECTION 		CAGE CODE: OD2L5	
				SIZE: N/A REV: N/A DWG NO. 85535 DO NOT SCALE THE DRAWING	