

# Push-On 75 Ohm F Male to F Female Adapter



# TECHNICAL DATA SHEET

PE9160

## Push-On 75 Ohm F Male to F Female Adapter

## Configuration

Connector 1F MaleImpedance 175 OhmsConnector 2F FemaleImpedance 275 OhmsAdapter DesignStandardBody StyleStraight

# **Mechanical Specifications**

#### Size

Length, in [mm] 0.928 [23.57] Width/Dia., in [mm] 0.432 [10.97]

#### **Connector 1**

Type F Male

Inner Conductor Material and Plating

Body Material and Plating

Dielectric Type

Phosphor Bronze, Tin

Brass, Nickel

Delrin

## Connector 2

Type F Female

Inner Conductor Material and Plating

Phosphor Bronze, Tin
Body Material and Plating

Brass, Nickel

Dielectric Type F

# Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

#### **Plotted and Other Data**

Notes: Values at 25 °C, sea level

URL: http://www.pasternack.com/f-male-f-female-straight-adapter-pe9160-p.aspx

Push-On 75 Ohm F Male to F Female Adapter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



# **PE9160 CAD Drawing**Push-On 75 Ohm F Male to F Female Adapter

