



4 Section Bandpass Filter With SMA Female Connectors Operating From 1.71 GHz To 1.77 GHz With a 60 MHz Passband

TECHNICAL DATA SHEET PI

PE8710

P/N: PE8710 1710 - 1770 MHz

4 Section Bandpass Filter With SMA Female Connectors Operating From 1.71 GHz To 1.77 GHz With a 60 MHz Passband

Configuration

Design	Combline Filter
Connector 1	SMA Female
Connector 2	SMA Female
Passband Frequency Range, GHz	1.71 to 1.77

Electrical Specifications

otriodi opodinodilorio	
Passband Minimum Frequency, GHz	1.71
Passband Maximum Frequency, GHz	1.77
Impedance, Ohms	50
Maximum Insertion Loss, dB	1.5
Passband Maximum VSWR	1.5:1
Maximum Input Power, Watts	5
Rejection at 1.49 GHz	50 dB
Rejection at 1.99 GHz	50 dB

Mechanical Specifications

Connector 1

Type SMA Female

Connector 2

Type SMA Female

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

Plotted and Other Data

Notes: Values at 25 °C, sea level

URL: http://www.pasternack.com/4-section-band-pass-filter-1.71-ghz-1.77-ghz-passband-60-mhz-pe8710-p.aspx

4 Section Bandpass Filter With SMA Female Connectors Operating From 1.71 GHz To 1.77 GHz With a 60 MHz Passband from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



PE8710 CAD Drawing

4 Section Bandpass Filter With SMA Female Connectors Operating From 1.71 GHz To 1.77 GHz With a 60 MHz Passband

