



PART TABLE

Model	Frequency Range
CSH-1	54-60 MHz
CSH-2	61-67 MHz
CSH-3	65-71 MHz
CSH-4	66-72 MHz
CSH-5	67-73 MHz
CSH-6	77-83 MHz
CSH-14	82-88 MHz
CSH-7	87-93 MHz
CSH-8	96-104 MHz
CSH-9	100-110 MHz
CSH-10	123-133 MHz
CSH-11	175-185 MHz

SPECIFICATIONS

Frequency Range: See Table
 Reverse Isolation: 20dB
 Insertion loss: 0.80dB Max.
 VSWR: 1.20:1
 Forward Power: 500W CW
 Operating Temperature: -10°C to +65°C

MATERIAL:		MICROWAVE COMMUNICATIONS LABORATORIES INC. 7250 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 544-6254 FAX: (727) 381-0110 http://www.mcli.com		SCALE: N/A
UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR (mm) (MILLIMETERS) FRACTIONS: ± 1/64 DECIMALS: ± .02 ± .008 ANGLE: ± 1/2°		DRAWING TITLE: LUMPED ELEMENT COAXIAL CIRCULATOR		SHEET: N/A
DRAWING: Paiboon Luekhamhan		DATE: 11-06-2012		PART NO.: CSH-XX/XX
APPROVED: T. Nguyen		DATE: 11-06-2012		CAGE CODE: OD2L5
				SIZE: N/A
				REV: N/A
				DWG NO.: 86184
DO NOT SCALE THE DRAWING				