

## 75 Ohm BNC Male Connector Crimp/Solder Attachment For RG11



## TECHNICAL DATA SHEET

PE4600

## 75 Ohm BNC Male Connector Crimp/Solder Attachment For RG11

Configuration

Connector BNC Male
Connector Interface Type RG11
Cable Attachment Method (Shield/Contact) Crimp/Solder
Body Style Straight

**Electrical Specifications** 

Frequency Range, MHz

Impedance, Ohms

Maximum Operating Voltage, Volts

Dielectric Withstanding Voltage, Vrms

DC to 1,000

75

500

1,500

**Mechanical Specifications** 

**Temperature** 

Operating Range, deg C -65 to +165

Size

 Length, in [mm]
 1.24 [31.5]

 Width/Dia., in [mm]
 0.57 [14]

 Weight, lbs [g]
 0.034 [15.42]

Connector

Type **BNC Male** Contact Material and Plating Brass, Gold **Contact Plating Specification** 30µ in. minimum Coupling Nut Material and Plating Brass, Nickel Coupling Nut Plating Specification 100µ in. minimum Body Material and Plating Brass, Nickel **Body Plating Specification** 100µ in. minimum Dielectric Type Teflon

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

**Plotted and Other Data** 

Notes: Values at 25 °C, sea level

URL: http://www.pasternack.com/bnc-male-standard-rg11-connector-pe4600-p.aspx

75 Ohm BNC Male Connector Crimp/Solder Attachment For RG11 from Pasternack Enterprises has same day shipment for domestic and International orders. We maintain 99% availability of the industry's broadest selection of RF, microwave and fiber optic products.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

ISO 9001 : 2008 Registered

## PE4600 CAD Drawing

75 Ohm BNC Male Connector Crimp/Solder Attachment For RG11

