

SPECIFICATION SHEET
JFW MODEL 50T-507-XXX
TERMINATION/MISMATCH

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range	DC-3000 MHz
Impedance	50 Ohms (referenced)
Available VSWR Values	1.0:1 through 5.0:1 in any 0.1 increment (1.0:1 = termination)
VSWR Tolerance (Termination)	1.15:1 maximum (50T-507-1.0)
VSWR Tolerance (Mismatches)	± 10% from mismatch value
RF Input Power	40 Watts average @ +25°C Derate to 20 Watts @ +70°C
Peak Power	1000 Watts (1 microsecond pulse)
RF Connector	N, TNC, BNC, SMA or 7/16 (male or female)
Operating Temperature Range	-55°C to +100°C
Physical Size	See outline drawing 092-6229

XXX - Insert VSWR value required.
Other values available upon request.

Example Model Numbers:

50T-507-1.0 N M	Termination (1.0:1) with N male
50T-507-1.5 SMA M	1.5:1 mismatch with SMA male
50T-507-3.2 TNC F	3.2:1 mismatch with TNC female
50T-507-5.0 BNC F	5.0:1 mismatch with BNC female

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	02/03/2010	O	SMR 02/04/2010				
19313	10/25/2010	A	TRS 10/25/2010				
23288	09/30/2013	B	TRS 09/30/2013				