

Frequency Synthesizer

KSN-3075A-119+

50Ω 2975 to 3045 MHz

The Big Deal

- Fractional N synthesizer
- Low phase noise and spurious
- Robust design and construction
- Small size 0.80" x 0.58" x 0.24"



CASE STYLE: DK1182

Product Overview

The KSN-3075A-119+ is a Frequency Synthesizer, designed to operate from 2975 to 3045 MHz for WiMAX 3.5GHz application. The KSN-3075A-119+ is packaged in a metal case (size of 0.80" x 0.58" x 0.24") to shield against unwanted signals and noise.

Key Features

Feature	Advantages
Low phase noise and spurious: • Phase Noise: -96 dBc/Hz typ. @ 10 kHz offset • Step Size Spurious: -98 dBc typ. • Comparison Spurious: -92 dBc typ. • Reference Spurious: -92 dBc typ.	Low phase noise and spurious improve system EVM (Error Vector Magnitude).
Robust design and construction	To enhance the robustness of KSN-3075A-119+, each internal component is secured to the substrate with chip bonder, thereby eliminating the risk of tombstoning during subsequent solder reflow operations by the customer.
Small size, 0.80" x 0.58" x 0.24"	The small size enables the KSN-3075A-119+ to be used in compact designs.



IF/RF MICROWAVE COMPONENTS • ISO 9001 ISO 14001 AS9100 CERTIFIED RoHS compliant
P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661



The Design Engineers Search Engine finds the model you need, Instantly • For detailed performance specs & shopping online see



Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.

- Fractional N synthesizer
- Integrated VCO + PLL
- Low phase noise and spurious
- Robust design and construction
- Low operating voltage (VCC VCO=+5V, VCC PLL=+3V)
- Small size 0.80" x 0.58" x 0.24"



PRICE: \$29.95 ea. QTY (1-9)

+ RoHS compliant in accordance
with EU Directive (2002/95/EC)

The +Suffix has been added in order to identify RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications.

- WiMAX 3.5GHz

The KSN-3075A-119+ is a Frequency Synthesizer, designed to operate from 2975 to 3045 MHz for WiMAX 3.5GHz application. The KSN-3075A-119+ is packaged in a metal case (size of 0.80" x 0.58" x 0.24") to shield against unwanted signals and noise. To enhance the robustness of KSN-3075A-119+, each internal component is secured to the substrate with chip bonder, thereby eliminating the risk of tombstoning during subsequent solder reflow operations by the customer.

The diagram illustrates a Phase-Locked Loop (PLL) system. An external crystal oscillator (F_{REF} XTAL) provides a reference signal (REF In) to the PLL. The PLL block contains a $1/R$ R Counter, a $K\Phi$ Phase Detector / Charge Pump, and a $1/N$ N Counter. The PLL is powered by VCC PLL and has control pins LE, DATA, CLOCK, and LOCK DET. The output of the PLL (CP) goes to a Loop Filter, which then feeds the VCO. The VCO is powered by VCC VCO and has a control pin VP. The VCO output goes through a Splitter to produce the RF Out signal. The PLL also has a feedback path from RF Out through a Splitter and a capacitor to its input (REF In).



IF/RF MICROWAVE COMPONENTS • ISO 9001 ISO 14001 AS9100 CERTIFIED **RoHS compliant**
P.O. Box 350166 Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661



2 The Design Engineers Search Engine finds the model you need. Instantly • For detailed performance specs & shopping online see

minicircuits.com

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuits' applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"). Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCISStore/terms.jsp

REV. A
M129408
EDR-8753/1A
KSN-3075A-119+
Category-A3
RAV
101027
Page 2 of 11

Electrical Specifications (over operating temperature -40°C to +85°C)

Parameters		Test Conditions	Min.	Typ.	Max.	Units
Frequency Range		-	2975	-	3045	MHz
Step Size		-	-	250	-	kHz
Comparison Frequency		-	-	20	-	MHz
Settling Time		Within ± 1 kHz	-	6	-	mSec
Output Power		-	0	+3	+6	dBm
SSB Phase Noise	@ 100 Hz offset		-	-76	-	dBc/Hz
	@ 1 kHz offset		-	-91	-83	
	@ 10 kHz offset		-	-96	-92	
	@ 100 kHz offset		-	-124	-120	
	@ 1 MHz offset		-	-144	-140	
Integrated SSB Phase Noise		@1 kHz to 5.5 kHz	-	-46	-43	dBc
Step Size Spurious Suppression		Step Size 250 kHz	-	-98	-82	dBc
0.5 Step Size Spurious Suppression		0.5 Step Size 125 kHz	-	-83	-65	
Reference & Comparison Spurious Suppression		Ref. & Comp. Freq. 20 MHz	-	-92	-70	
Non - Harmonic Spurious Suppression		-	-	-90	-	
Harmonic Suppression		-	-	-30	-23	V
VCO Supply Voltage		+5.00	+4.90	+5.00	+5.10	
PLL Supply Voltage		+3.00	+2.85	+3.00	+3.15	mA
VCO Supply Current		-	-	45	52	
PLL Supply Current		-	-	15	23	
Reference Input (External)	Frequency	20 (square wave)	-	20	-	MHz
	Amplitude	1	-	1	-	V _{P-P}
	Input impedance	-	-	100	-	K Ω
	Phase Noise @ 1 kHz offset	-	-	-145	-	dBc/Hz
RF Output port Impedance		-	-	50	-	Ω
Input Logic Level	Input high voltage	-	2.55	-	-	V
	Input low voltage	-	-	-	0.55	V
Digital Lock Detect	Locked	-	2.45	-	3.15	V
	Unlocked	-	-	-	0.40	V
Frequency Synthesizer PLL		-	ADF4153			
PLL Programming		-	3-wire serial 3V CMOS			
Register Map @ 3045 MHz	R0_Register	-	(MSB) 1001100000000001010000 (LSB)			
	R1_Register	-	(MSB) 101000100000101000001 (LSB)			
	R2_Register	-	(MSB) 1111100010 (LSB)			
	R3_Register	-	(MSB) 1111000111 (LSB)			

Absolute Maximum Ratings

Parameters	Ratings
VCO Supply Voltage	5.6V
PLL Supply Voltage	4.0V
VCO Supply Voltage to PLL Supply Voltage	-0.3V to +5.8V
Reference Frequency Voltage	-0.3Vmin, VCC PLL +0.3Vmax
Data, Clock, LE Levels	-0.3Vmin, VCC PLL +0.3Vmax
Operating Temperature	-40°C to +85°C
Storage Temperature	-55°C to +100°C

Permanent damage may occur if any of these limits are exceeded



IF/RF MICROWAVE COMPONENTS • ISO 9001 ISO 14001 AS9100 CERTIFIED RoHS compliant

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661



The Design Engineers Search Engine finds the model you need, Instantly • For detailed performance specs & shopping online see minicircuits.com

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.

Typical Performance Data

FREQUENCY (MHz)	POWER OUTPUT (dBm)			VCO CURRENT (mA)			PLL CURRENT (mA)		
	-45°C	+25°C	+85°C	-45°C	+25°C	+85°C	-45°C	+25°C	+85°C
2975	2.96	2.68	1.89	44.04	45.87	47.18	13.45	15.16	17.50
2983	3.00	2.71	1.96	44.02	45.91	47.18	13.32	15.04	17.35
2992	3.04	2.76	2.03	44.03	45.91	47.17	13.48	15.20	17.52
3001	3.08	2.77	1.99	44.04	45.90	47.25	13.16	14.87	17.17
3010	3.04	2.76	2.06	44.02	45.90	47.16	13.53	15.26	17.58
3019	2.92	2.68	2.00	44.03	45.89	47.15	13.20	14.92	17.22
3028	2.81	2.57	1.90	44.02	45.88	47.14	13.45	15.19	17.50
3037	2.72	2.45	1.83	43.99	45.90	47.13	13.34	15.07	17.38
3045	2.76	2.42	1.79	43.97	45.87	47.12	13.39	15.11	17.44

FREQUENCY (MHz)	HARMONICS (dBc)					
	F2			F3		
	-45°C	+25°C	+85°C	-45°C	+25°C	+85°C
2975	-35.01	-45.20	-52.91	-30.98	-38.29	-35.29
2983	-34.62	-45.52	-51.53	-31.97	-38.26	-36.11
2992	-34.64	-46.04	-51.93	-31.99	-37.98	-36.08
3001	-34.94	-46.24	-49.47	-32.78	-38.21	-36.18
3010	-34.85	-45.90	-49.50	-33.54	-39.27	-37.03
3019	-34.80	-45.72	-49.15	-33.41	-39.64	-37.55
3028	-35.32	-46.70	-46.47	-33.45	-39.33	-37.79
3037	-36.38	-48.69	-44.92	-34.22	-39.27	-38.44
3045	-37.08	-50.20	-44.61	-34.49	-39.05	-38.54



IF/RF MICROWAVE COMPONENTS • ISO 9001 ISO 14001 AS9100 CERTIFIED RoHS compliant

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661



The Design Engineers Search Engine finds the model you need, Instantly • For detailed performance specs & shopping online see



Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCStore/terms.jsp.

FREQUENCY (MHz)	PHASE NOISE (dBc/Hz) @ OFFSETS				
	+25°C				
	100Hz	1kHz	10kHz	100kHz	1MHz
2975	-82.56	-91.56	-97.12	-125.19	-145.66
2983	-82.35	-92.48	-96.78	-125.69	-145.64
2992	-81.51	-92.39	-96.65	-125.21	-145.56
3001	-81.98	-92.02	-96.44	-125.33	-145.56
3010	-81.65	-91.59	-96.34	-125.30	-145.38
3019	-80.93	-91.93	-95.72	-125.13	-145.59
3028	-83.11	-91.24	-96.87	-125.32	-145.64
3037	-81.73	-90.12	-96.52	-125.28	-145.36
3045	-81.34	-90.37	-96.33	-125.14	-145.36

FREQUENCY (MHz)	PHASE NOISE (dBc/Hz) @ OFFSETS				
	-45°C				
	100Hz	1kHz	10kHz	100kHz	1MHz
2975	-80.88	-89.79	-97.49	-125.41	-146.19
2983	-80.62	-90.21	-97.01	-125.39	-145.26
2992	-80.30	-89.76	-96.89	-125.47	-145.94
3001	-79.15	-89.75	-96.63	-125.39	-145.75
3010	-79.25	-89.17	-96.22	-125.32	-145.64
3019	-80.81	-88.20	-96.56	-125.19	-145.76
3028	-79.49	-89.80	-96.60	-125.07	-145.49
3037	-79.15	-88.54	-96.15	-125.13	-145.53
3045	-79.80	-89.72	-96.35	-125.20	-145.45

FREQUENCY (MHz)	PHASE NOISE (dBc/Hz) @ OFFSETS				
	+85°C				
	100Hz	1kHz	10kHz	100kHz	1MHz
2975	-82.23	-93.37	-97.07	-124.60	-144.71
2983	-82.16	-93.59	-96.92	-124.54	-144.72
2992	-80.93	-92.56	-96.47	-124.61	-144.85
3001	-82.34	-93.29	-96.38	-124.46	-144.77
3010	-81.99	-93.67	-96.42	-124.64	-144.46
3019	-81.29	-93.53	-96.15	-124.38	-144.51
3028	-82.26	-92.73	-96.57	-124.62	-144.57
3037	-82.13	-92.93	-96.14	-124.55	-144.67
3045	-81.43	-93.90	-96.93	-124.43	-144.78



IF/RF MICROWAVE COMPONENTS • ISO 9001 ISO 14001 AS9100 CERTIFIED RoHS compliant

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661



The Design Engineers Search Engine finds the model you need, Instantly • For detailed performance specs & shopping online see



Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.

REFERENCE & COMPARISON SPURIOUS ORDER n	REFERENCE & COMPARISON SPURIOUS @Fcarrier 2975MHz+(n*Freference) (dBc) note 1			REFERENCE & COMPARISON SPURIOUS @Fcarrier 3010MHz+(n*Freference) (dBc) note 1			REFERENCE & COMPARISON SPURIOUS @Fcarrier 3045MHz+(n*Freference) (dBc) note 1		
	-45°C	+25°C	+85°C	-45°C	+25°C	+85°C	-45°C	+25°C	+85°C
-5	-98.22	-96.45	-101.73	-98.66	-94.93	-100.28	-98.94	-96.08	-98.10
-4	-96.73	-92.94	-94.89	-95.68	-93.07	-93.84	-96.14	-93.89	-92.85
-3	-100.44	-95.70	-97.28	-98.09	-97.26	-94.21	-95.98	-94.90	-93.78
-2	-107.56	-106.37	-100.76	-113.24	-104.22	-100.71	-109.26	-101.61	-99.87
-1	-87.48	-91.38	-87.97	-88.58	-90.74	-88.49	-90.22	-92.56	-88.94
0 note 2	-	-	-	-	-	-	-	-	-
+1	-91.57	-94.20	-88.35	-95.28	-92.75	-90.12	-97.83	-95.40	-92.09
+2	-101.07	-105.54	-98.25	-104.73	-98.53	-100.16	-105.90	-99.86	-97.66
+3	-106.91	-100.08	-100.39	-104.52	-103.60	-98.08	-107.11	-101.39	-97.51
+4	-96.45	-95.72	-94.59	-97.94	-96.13	-93.83	-101.69	-94.67	-96.60
+5	-95.08	-98.65	-96.43	-96.15	-93.91	-97.81	-105.28	-95.17	-96.91

Note 1: Comparison frequency = reference frequency = 20 MHz

Note 2: All spurs are referenced to carrier signal (n=0).

STEP SIZE SPURIOUS ORDER n	0.5 STEP SIZE & STEP SIZE SPURIOUS @Fcarrier 2975MHz+(n*Fstep size) (dBc) note 3			0.5 STEP SIZE & STEP SIZE SPURIOUS @Fcarrier 3010MHz+(n*Fstep size) (dBc) note 3			0.5 STEP SIZE & STEP SIZE SPURIOUS @Fcarrier 3045MHz+(n*Fstep size) (dBc) note 3		
	-45°C	+25°C	+85°C	-45°C	+25°C	+85°C	-45°C	+25°C	+85°C
-5.0	-108.74	-111.32	-111.44	-110.76	-115.58	-108.55	-114.50	-112.84	-114.06
-4.5	-110.96	-112.69	-109.06	-109.26	-109.25	-111.76	-109.52	-108.79	-111.31
-4.0	-114.54	-115.33	-112.88	-112.88	-113.10	-114.23	-113.54	-110.54	-112.14
-3.5	-112.81	-113.91	-110.36	-106.03	-110.45	-107.49	-111.48	-109.46	-109.13
-3.0	-111.39	-109.44	-112.04	-111.16	-113.46	-112.31	-108.76	-106.94	-111.83
-2.5	-111.98	-109.17	-109.91	-110.54	-108.98	-107.30	-106.52	-104.56	-112.50
-2.0	-93.91	-99.75	-97.01	-97.82	-103.86	-105.92	-104.43	-101.75	-109.36
-1.5	-102.47	-101.19	-105.70	-101.49	-107.41	-100.72	-101.94	-104.47	-101.84
-1.0	-98.26	-94.60	-98.91	-97.54	-100.48	-97.48	-97.47	-100.47	-99.06
-0.5	-83.95	-86.44	-85.46	-84.35	-83.29	-84.03	-86.67	-83.57	-86.71
0 note 4	-	-	-	-	-	-	-	-	-
+0.5	-84.00	-85.37	-85.18	-86.08	-85.78	-84.71	-84.23	-86.23	-87.54
+1.0	-96.40	-99.58	-97.80	-95.80	-97.83	-99.13	-96.98	-94.83	-94.45
+1.5	-103.86	-106.91	-105.79	-103.32	-106.20	-101.47	-103.08	-102.93	-102.85
+2.0	-95.32	-98.95	-97.00	-100.85	-108.33	-107.14	-104.07	-101.75	-106.69
+2.5	-110.80	-111.52	-111.17	-110.56	-110.47	-109.22	-106.77	-103.45	-107.53
+3.0	-109.58	-112.19	-110.49	-106.49	-112.00	-112.30	-107.60	-109.22	-113.20
+3.5	-109.72	-115.14	-109.49	-106.43	-111.87	-109.28	-111.63	-107.84	-113.09
+4.0	-112.38	-113.47	-112.01	-112.88	-114.26	-113.23	-111.69	-111.37	-113.71
+4.5	-110.93	-113.69	-113.70	-110.12	-104.54	-110.68	-112.39	-107.89	-111.84
+5.0	-111.70	-115.00	-109.93	-111.91	-112.65	-111.46	-112.35	-109.63	-112.79

Note 3: Step size frequency 250 kHz

Note 4: All spurs are referenced to carrier signal (n=0).



IF/RF MICROWAVE COMPONENTS • ISO 9001 ISO 14001 AS9100 CERTIFIED RoHS compliant

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661




The Design Engineers Search Engine finds the model you need, Instantly • For detailed performance specs & shopping online see




Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.

Typical Performance Curves


OUTPUT POWER Vs FREQUENCY



2nd HARMONIC Vs FREQUENCY



3rd HARMONIC Vs FREQUENCY



IF/RF MICROWAVE COMPONENTS • ISO 9001 ISO 14001 AS9100 CERTIFIED RoHS compliant






P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661



The Design Engineers Search Engine finds the model you need, Instantly • For detailed performance specs & shopping online see



Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.



IF/RF MICROWAVE COMPONENTS • ISO 9001 ISO 14001 AS9100 CERTIFIED RoHS compliant
P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661




The Design Engineers Search Engine finds the model you need, Instantly • For detailed performance specs & shopping online see




Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCStore/terms.jsp.


REFERENCE & COMPARISON SPURIOUS
Vs FREQ. OFFSET @ Fcar = 2975MHz




0.5 STEP SIZE & STEP SIZE SPURIOUS
Vs FREQ. OFFSET @ Fcar = 2975MHz




REFERENCE & COMPARISON SPURIOUS
Vs FREQ. OFFSET @ Fcar = 3010MHz




0.5 STEP SIZE & STEP SIZE SPURIOUS
Vs FREQ. OFFSET @ Fcar = 3010MHz



REFERENCE & COMPARISON SPURIOUS
Vs FREQ. OFFSET @ Fcar = 3045MHz



0.5 STEP SIZE & STEP SIZE SPURIOUS
Vs FREQ. OFFSET @ Fcar = 3045MHz



IF/RF MICROWAVE COMPONENTS • ISO 9001 ISO 14001 AS9100 CERTIFIED RoHS compliant

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661




The Design Engineers Search Engine finds the model you need, Instantly • For detailed performance specs & shopping online see



Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.

Pin Configuration




Pin Connection

Pin Number	Function
1	VCC PLL
2	GND
3	REF IN
4	GND
5	VCC VCO
6	GND
7	RF OUT
8	GND
9	LOCK DET
10	CLOCK
11	DATA
12	LE
13	GND
14	GND

Recommended Application Circuit

Note: REF IN and RF OUT ports are internally AC coupled.



IF/RF MICROWAVE COMPONENTS • ISO 9001 ISO 14001 AS9100 CERTIFIED RoHS compliant
P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661




The Design Engineers Search Engine finds the model you need, Instantly • For detailed performance specs & shopping online see



Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCStore/terms.jsp.

Device Marking

**Additional Detailed Technical Information**

Additional information is available on our web site. To access this information enter the model number on our web site home page.

Case Style: DK1182

Tape & Reel: TR-F28

Suggested Layout for PCB Design: PL-249

Evaluation Board: TB-567-2+

Environment Ratings: ENV03T2



IF/RF MICROWAVE COMPONENTS • ISO 9001 ISO 14001 AS9100 CERTIFIED RoHS compliant

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661



The Design Engineers Search Engine finds the model you need, Instantly • For detailed performance specs & shopping online see



Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.