



## Precision SMA Female to ZMA Plug Adapter 3 Lug

## TECHNICAL DATA SHEET

PE91075

#### Precision SMA Female to ZMA Plug Adapter 3 Lug

Pasternack's ZMA Adapters use a clocked bayonet-style mating method suitable for applications requiring robust mechanical connections, such as high vibration and high coupling force environments. This line of ZMA adapters is designed for limited space applications requiring superb RF performance up to 18GHz and offer VSWR as low as 1.15:1. ZMA's 3-Lug or 4-Lug designs can be mated by hand with one-third or one-quarter turn, respectively -no special tooling is required.

- · Available in 18 GHz SMA-ZMA Configurations
- 3-Lug or 4-Lug Options Available
- · Passivated Stainless Steel Bodies with Gold Plated Center Contacts
- VSWR as low as 1.15
- · Bayonet Style Interface decreases mechanical deterioration in heavy-use test environments

### Configuration

Connector 1 **SMA Female** 50 Ohms Impedance 1 Connector 2 ZMA Plug Impedance 2 50 Ohms Adapter Design Precision Body Style Straight

## **Electrical Specifications**

Frequency Range, GHz DC to 18 Maximum VSWR 1.15:1 Maximum Insertion Loss, dB 0.21

#### **Mechanical Specifications**

Temperature

Operating Range, deg C -55 to +100

Length, in [mm] 0.983 [24.97]

Connector 1

**SMA Female** Inner Conductor Material and Plating Beryllium Copper, Gold Inner Conductor Plating Specification MIL-G-45204 Outer Conductor Material and Plating Passivated Stainless Steel Outer Conductor Plating Specification ASTM A380 Body Material and Plating Passivated Stainless Steel

**Body Plating Specification** ASTM A380

Dielectric Type **PTFE** 

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Precision SMA Female to ZMA Plug Adapter 3 Lug PE91075

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal

ISO 9001: 2008 Registered





## Precision SMA Female to ZMA Plug Adapter 3 Lug

# TECHNICAL DATA SHEET

PE91075

#### **Connector 2**

Type
Inner Conductor Material and Plating
Inner Conductor Plating Specification
Coupling Nut Material and Plating
Coupling Nut Plating Specification
Body Material and Plating
Dielectric Type

ZMA Plug Beryllium Copper, Gold MIL-G-45204 Passivated Stainless Steel ASTM A830 Passivated Stainless Steel PTFE

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant

Yes

**Plotted and Other Data** 

Notes:

Values at 25 °C, sea level

Precision SMA Female to ZMA Plug Adapter 3 Lug from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Precision SMA Female to ZMA Plug Adapter 3 Lug PE91075

URL: http://www.pasternack.com/sma-female-zma-plug-straight-adapter-pe91075-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



**PE91075 CAD Drawing**Precision SMA Female to ZMA Plug Adapter 3 Lug

