The MTPA20010250471 is a completely solid state microwave power amplifier module which features high efficiency, high output power and wide dynamic range. It uses advanced microwave device technology and provides high reliability and ruggedness product for our customer. MTPA20010250471 has the function of over current and over temperature protection to guarantee the safety of working in various harsh conditions.

- ·20MHz~1GHz ultra-broadband
- Psat:50W
- High efficiency, High reliability and ruggedness
- Good linearity, Low distortion
- Applications: Test & Measurement, Broadcasting, Communication, etc



ELECTRICAL CHARACTERISTICS @ 28V AC +25° C 50Ω

PARAMETER	UNIT	MIN	TYPICAL	MAX
Frequency Response	MHz	20		1000
Power Gain	dB	48	51	54
Gain Flatness per 40 MHz bandwidth	+/-dB		1	
Gain Flatness via Temperature	+/-dB			2
Saturated Output Power@20- 500MHz	dBm	60	75	
Saturated Output Power@500- 1000MHz		80	100	
Efficiency @ Sat Output Power	%		25	
Output Power @ 1dB gain compression point	dBm	40	50	
Harmonic Distortion	dBc		-20	
Spurious Signals	dBc		-60	
IM3@P1dB	dBc		-25	
Input For Rated Output Power	dBm		+5	
Input VSWR			1.5: 1	2: 1
Output VSWR			2: 1	

ENVIRONMENTAL SPECIFICATIONS (DESIGN TO MEET)

PARAMETER	UNIT	MIN	TYPICAL	MAX
Voltage	V (AC)		28	
Current	Α		1.5	
Operating Temperature	°C	0		50
Non-Operating Temperature	°C	-40		70

MECHANICAL SPECIFICATIONS

PARAMETER	UNIT	MIN	TYPICAL	MAX
Dimensions W x H x D	Inch		6.60X5.80X1.00	
Weight	Kg		1	
RF Input & Output			SMA(F), SMA(F)	

|--|



OUTLINE DRAWINGS

