

AMP2050

SOLID STATE HIGH POWER AMPLIFIER

FEATURES

Rack mount system
Class AB linear GaN design
Instantaneous wide bandwidth
Suitable for all modulations standards
Built-in protection circuits
High reliability and ruggedness



ELECTRICAL SPECIFICATIONS

Parameter	Specification	Notes
Operating Frequency Range	4.0 - 8.0 GHz	
Power Output @ P1dB GCP	20 Watt Min	CW
Power Gain	43 dB Min	
Gain Adjustment Range	10 dB Min	Manual or Remote
Power Gain Flatness	4.0 dB p-p	
Input Return Loss	12 dB Min	Relative to 50 Ohm
2-Tone Intermodulation (IMD)	>30 dBc Typ	36dBm/Tone, $\Delta = 1\text{MHz}$
Harmonics	>20 dBc Typ	At rated output power
Non Harmonics Spurious	>60dBc	
Operating Voltage	100 - 240 VAC	Single phase
Power Consumption	400 Watt Max	At Rated Pout
Max Input Power	+8 dBm	Without damage
Load VSWR Protection	$\infty : 1$	

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Ambient Temperature	0 to +50 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	5 to 95 %	Non Condensing

MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions W x H x D	430 x 88 x 562 mm	2U
Weight	10 kg.	
RF Connectors In/Out	Type-N Female	
AC Power / Interface Connector	IEC 60320-C14 / 9-Pin D-Sub	
Cooling	Built in Fan Cooling	Variable speed
OPTIONAL: Digital Control: FWD, REV, VSWR, GAIN, ALC, V & I, TEMP	Ethernet RJ-45 TCP/IP, RS422/485, GPIB Interface	Remote Bluetooth application

AMP2050 SOLID STATE HIGH POWER AMPLIFIER

OUTLINE DRAWING

