

SPECIFICATION SHEET
JFW MODEL 50DR-055
DUAL ROTARY ATTENUATOR

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range DC-2000 MHz

Impedance 50 Ohms nominal

Attenuation Range 0-30 dB in 1 dB steps

VSWR 1.3:1 maximum DC-1000 MHz
1.5:1 maximum 1000-2000 MHz

Insertion Loss 0.8 dB maximum

Attenuation Accuracy ± 0.25 dB or 2% DC-1000 MHz
 ± 0.40 dB or 3% 1000-2000 MHz
(whichever is greater)

RF Input Power 2 Watts average
1000 Watts peak

Direction of Rotation Attenuation increases in a Clockwise direction

Indexing 30 degrees with stops at
Minimum and maximum

RF Connector* SMA, BNC, TNC, RPT, N or 4.1/9.5 Mini-DIN
female

RPT female = Reverse Polarity TNC female
(female body/male pin)

Operating Temperature Range -20°C to +85°C

Knob/Panel Mounting Drawing 092-8435-02

Outline Drawings 092-1748 (50DR-055 SMA)
092-5760 (50DR-055 BNC)
092-6720 (50DR-055 N)
092-6733 (50DR-055 RPT)
092-8367 (50DR-055 4.1/9.5)

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
9999	05/12/2003	B	BAC 02/05/2004	19178	09/28/2010	E	TRS 09/28/2010
15655	04/09/2008	C	TRS 04/09/2008	25572	07/28/2015	F	TRS 07/28/2015
19163	09/22/2010	D	TRS 09/22/2010	25776	09/28/2015	G	TRS 09/29/2015