


剥线尺寸
stripping dimension



产品型号 type	电缆型号 cable type	备注 remark
SMB-KWB2A	SFT-50-2-1、RG405/U	
SMB-KWB2N		壳体:镀镍 body:nickel plated

Electrical Characteristics:

- Characteristic Impedance: $50\ \Omega$
- Frequency range: DC~3GHz
- Contact resistance
Center conductor: $\leq 6.0\ m\Omega$
Out conductor: $\leq 1.0\ m\Omega$
- Insulation resistance: $\geq 1000M\Omega$
- Insulator withstanding: 750V
- VSWR: ≤ 1.4
- Durability: 500cycles

主要性能指标

- 特性阻抗: $50\ \Omega$
- 频率范围: DC~3GHz
- 接触电阻:
中心导体: $\leq 6.0\ m\Omega$
外导体: $\leq 1.0\ m\Omega$
- 绝缘电阻: $\geq 1000M\Omega$
- 介质耐压: 750V
- 电压驻波比: ≤ 1.4
- 插拔次数: 500次

Application: MIL-C-39012/68A


执行标准: MIL-C-39012/68A

Material&Finishing

- Center contact:
Female: beryllium copper, gold plated
- Body: brass, gold plated
- Insulators: PTFE

材料和镀层

- 中心接触件:
插孔: 铍青铜, 镀金
- 壳体: 黄铜, 镀金
- 绝缘子: 聚四氟乙烯

		SCALE		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE mm, TOLERANCES ARE FRACTIONS DECIMALS ANGLES .X± .15 ±1° .XX± .05 .XXX±
		4:1		
	NAME	DATE	SMB-KWB2A RF COAXIAL CONNECTOR	
DRAWN				
CHECKED				
APPROVED				
				西安富士达科技股份有限公司 XI'AN FORSTAR S&T CO.,LTD.