



# SMP Male Limited Detent Connector Solder Attachment Thru Hole PCB, Square Body, Up To 8 GHz

### TECHNICAL DATA SHEET

PE44776

Pasternack 8 GHz SMP connectors are designed to offer a low cost alternative where the SMP form factor is desired but the standard SMP frequency range is not needed. The line of 8 GHz SMP connectors is fully compatible with industry standard SMP and GPO® connectors. These SMP connectors offer a low cost high performance blind-mate solution for lower frequency applications. The Male versions of the 8 GHz SMP is available in Full Detent, Limited Detent, and Smooth Bore versions.

- Fully compatible with industry standard SMP and GPO® connectors
- Full Detent, Limited Detent, and Smooth Bore Male designs
- Glass Bead Hermetic Sealed Male Shroud versions available
- DC to 8 GHz with excelent VSWR and RF Leakage performance

#### Configuration

Connector SMP Male, Limited Detent
Connector Specification MIL-STD-348A
Connector Interface Type Thru Hole
Cable Attachment Method (Shield/Contact) Solder
Body Style Straight

#### **Electrical Specifications**

Frequency Range, GHz
Impedance, Ohms
Maximum VSWR
DC to 8
50
1.1:1

### **Mechanical Specifications**

Temperature

Operating Range, deg C -55 to +155

Size

 Length, in [mm]
 0.279 [7.09]

 Width/Dia., in [mm]
 0.236 [5.99]

 Height, in [mm]
 0.236 [5.99]

Connector

Type SMP Male Mating Cycles 500

Contact Material and Plating
Contact Plating Specification
Body Material and Plating
Brass, Gold
Brass, Gold

Body Plating Specification MIL-DTL-45204
Dielectric Type PEI

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMP Male Limited Detent Connector Solder Attachment Thru Hole PCB, Square Body, Up To 8 GHz PE44776

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

ISO 9001 : 2008 Registered





# SMP Male Limited Detent Connector Solder Attachment Thru Hole PCB, Square Body, Up To 8 GHz

### TECHNICAL DATA SHEET

PE44776

#### **Plotted and Other Data**

Notes:

Values at 25 °C, sea level GPO® is a Registered Trademark of Corning Gilbert Inc.

SMP Male Limited Detent Connector Solder Attachment Thru Hole PCB, Square Body, Up To 8 GHz from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMP Male Limited Detent Connector Solder Attachment Thru Hole PCB, Square Body, Up To 8 GHz PE44776

URL: http://www.pasternack.com/smp-male-standard-thru-hole-pcb-connector-pe44776-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



ISO 9001: 2008 Registered

# PE44776 CAD Drawing

SMP Male Limited Detent Connector Solder Attachment Thru Hole PCB, Square Body, Up To 8 GHz

