


REVISIONS				
ZONE	REV	DESCRIPTION	Date	APPROVED



SPECIFICATIONS

Frequency Range: 3.4–4.2 GHz
 Isolation: 22dB Min.
 Insertion loss: 0.5dB Max.
 VSWR: 1.18:1 Max.
 Average Power: 1 Watt
 Operating Temperature: 0°C to +85°C

MATERIAL:		MCLI MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM		SCALE: N/A	
				SHEET: N/A	
UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR (mm) (MILLIMETERS) FRACTIONS: $\pm 1/64$ DECIMALS: $\pm .01 \pm .005$ ANGLE: $\pm 1/2^\circ$		DRAWING TITLE: COAXIAL ISOLATOR			
		PART NO. IS-189/NMO			
DRAWN: Paiboon Luekhamhan DATE: 04-04-2013		CAGE CODE: OD2L5 SIZE: N/A REV: N/A DO NOT SCALE THE DRAWING		DWG NO. 86265	
APPROVED: T. Nguyen DATE: 04-04-2013		THIRD ANGLE PROJECTION			