

1 Watt RF Load Up To 18 GHz With SMA Female Input Passivated Stainless Steel



RF Terminations Technical Data Sheet

PE6073

Configuration

RF Load Design Precision
Connector SMA Female
Connector Specification MIL-STD-348

Heat Sink Passivated Stainless Steel

Connection Method Standard Body Style Straight

Electrical Specifications (Values at 25°C, sea level)

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		18	GHz
Impedance		50	100	Ohms
VSWR			1.25:1	
Input Power		A	1	Watts

Mechanical Specifications

Size

 Length
 0.545 in [13.84 mm]

 Width/Dia.
 0.25 in [6.35 mm]

Connector

Type SMA Female

Body Material and Plating Passivated Stainless Steel

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant

REACH Compliant 06/18/2012

Plotted and Other Data

Notes

• Values at +25 °C, sea level

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 1 Watt RF Load Up To 18 GHz With SMA Female Input Passivated Stainless Steel PE6073

PE6073 REV 1.2



ISO 9001 : 2008 Registered



P

1 Watt RF Load Up To 18 GHz With SMA Female Input Passivated Stainless Steel

RF Terminations Technical Data Sheet

PE6073

1 Watt RF Load Up To 18 GHz With SMA Female Input Passivated Stainless Steel from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 1 Watt RF Load Up To 18 GHz With SMA Female Input Passivated Stainless Steel PE6073

URL: http://www.pasternack.com/1-watts-sma-female-rf-load-up-to-18-ghz-precision-pe6073-p.aspx

PE6073 REV 1.2

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623

Phone: (866) 727-8376 or (949) 261-1920 • Fax: (949) 261-7451

Sales@Pasternack.com • Techsupport@Pasternack.com



ISO 9001 : 2008 Registered

PE6073 CAD Drawing

1 Watt RF Load Up To 18 GHz With SMA Female Input Passivated Stainless Steel

