



## 0 to 1 dB Rotary Step Attenuator, 75 Ohm BNC Female To 75 Ohm BNC Female With 0.1 dB Step Rated To 1 Watt Up To 1 GHz

### TECHNICAL DATA SHEET

PE7035-5

0 to 1 dB Rotary Step Attenuator, 75 Ohm BNC Female To 75 Ohm BNC Female With 0.1 dB Step Rated To 1 Watt Up To 1 GHz

Configuration

Design Step, Bidirectional Attenuator

Connector 1 BNC Female
Connector 2 BNC Female

**Electrical Specifications** 

Frequency Range, MHz DC to 1,000

Impedance, Ohms 75
Attenuation Value, dB 0 to 1
Step Size, dB 0.1
Step Type Rotary
Maximum Input Power Watts

Maximum Input Power, Watts 1
Maximum VSWR 1.4:1

Frequency 1

 Range, MHz
 DC to 500

 VSWR
 1.3:1

 Attenuation Accuracy, dB
 ± 0.07

Frequency 2

Range, MHz 500 to 1,000 VSWR 1.4:1 Attenuation Accuracy, dB  $\pm$  0.07

**Mechanical Specifications** 

**Temperature** 

Operating Range, deg C -20 to +85

Size

 Length, in [mm]
 4.5 [114.3]

 Width, in [mm]
 4 [101.6]

 Height, in [mm]
 4 [101.6]

Connector 1

Type BNC Female

Connector 2

Type BNC Female

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 0 to 1 dB Rotary Step Attenuator, 75 Ohm BNC Female To 75 Ohm BNC Female With 0.1 dB Step Rated To 1 Watt Up To 1 GHz PE7035-5

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

ISO 9001 : 2008 Registered





# 0 to 1 dB Rotary Step Attenuator, 75 Ohm BNC Female To 75 Ohm BNC Female With 0.1 dB Step Rated To 1 Watt Up To 1 GHz

### **TECHNICAL DATA SHEET**

PE7035-5

Compliance Certifications (visit www.Pasternack.com for current document)

**Plotted and Other Data** 

Notes:

Values at 25 °C, sea level

0 to 1 dB Rotary Step Attenuator, 75 Ohm BNC Female To 75 Ohm BNC Female With 0.1 dB Step Rated To 1 Watt Up To 1 GHz from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 0 to 1 dB Rotary Step Attenuator, 75 Ohm BNC Female To 75 Ohm BNC Female With 0.1 dB Step Rated To 1 Watt Up To 1 GHz PE7035-5

URL: http://www.pasternack.com/1db-step-bnc-female-bnc-female-1-watt-attenuator-pe7035-5-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



### PE7035-5 CAD Drawing

0 to 1 dB Rotary Step Attenuator, 75 Ohm BNC Female To 75 Ohm BNC Female With 0.1 dB Step Rated To 1 Watt Up To 1 GHz

