

5300 Beethoven Street, Los Angeles, CA 90066 TEL: (310)306-5556 • FAX: (310)821-7413 WEB: www.ophirrf.com • E-MAIL: sales@ophirrf.com

MODEL 5126-030

20 - 1000 MHz **120 WATTS** LINEAR POWER RF AMPLIFIER

Solid State Broadband High Power RF Amplifier

The 5126-030 is a 120 Watt broadband amplifier that covers the 20 - 1000 MHz frequency range. This small lightweight amplifier and utilizes Class A/AB linear power devices that provide 3rd excellent order intercept point, high gain, and a wide dynamic range.

Due to robust engineering and employment of the most advanced devices and components, this amplifier efficiency achieves high operation with proven reliability. Like all OPHIR_{RF} amplifiers. the 5126-030 comes with an extended multiyear warranty.

	<u>Parameter</u>	Specification @ 25° C
Electrical		
1	Frequency Range	20 – 1000 MHz
2	Saturated Output Power	120 Watts rated
3	Power Output @ 1dB Comp.	70 Watts min
4	Small Signal Gain	+52 dB min
5	Small Signal Gain Flatness	<u>+</u> 2.0 dB max
6	IP ₃	+55 dBm typical
7	Input VSWR	2:1 max
8	Harmonics	-20 dBc typical @ 70 Watts
9	Spurious Signals	< -60 dBc typical @ 70 Watts
10	Input/Output Impedance	50 Ohms nominal
11	AC Input Power	1500 Watts max
12	AC Input	100 – 240 VAC, single phase
13	RF Input	0 dBm max
14	RF Input Signal Format	CW/AM/FM/PM/Pulse
15	Class of Operation	AB
<u>Mechanical</u>		
16	Dimensions	19" x 7.0" x 20"
17	Weight	60 lb. max
18	Connectors	Type-N
19	Chassis Slides	18" (37" wingspan)
20	Grounding	Chassis
21	Cooling	Internal Forced Air
<u>Environmental</u>		
22	Operating Temperature	0° C to +50° C
23	Operating Humidity	95% Non-condensing
24	Operating Altitude	Up to 10,000' Above Sea Level
25	Shock and Vibration	Normal Truck Transport
CUIT PROTECTIONS Specifications subject to change without notice.		

CIRCUIT INDICATIONS

- ♦ Forward Power
- ♦ Reflected power
- ♦ VSWR Fault
- ♦ Temp Fault

04/10

♦ Gain Setting (VVA) percentage

CIRCUIT PROTECTIONS

- ♦ Thermal Overload
- ♦ Over Current
- ♦ Over Voltage

ORDERING MODELS

- ♦ RE - R model with Ethernet, IEEE488 and RS232
- ♦ FE - F model with Ethernet, IEEE488 and RS232

-030 Feature: Chassis Mount Slides, 18"



Approved By: Date: