

Ceramic

Frequency Mixer WIDE BAND

MCA1T-60MH+

Level 13 (LO Power+13 dBm) 1700 to 6000 MHz


Maximum Ratings

Operating Temperature	-40°C to 85°C
Storage Temperature	-40°C to 85°C
RF Power	200 mW
IF Current	40 mA
Permanent damage may occur if any of these limits are exceeded.	

Pin Connections

LO	10
RF	5
IF	3
GROUND	1,2,4,6,7,8,9


Outline Drawing



Outline Dimensions (inch)

A	B	C	E	F	G
.350	.280	.095	.075	.050	.030
8.89	7.11	2.41	1.91	1.27	0.76
H	K	L	M	wt	
.074	.096	.321	.030	grams	
1.88	2.44	8.15	0.76	0.21	

Demo Board MCL P/N: TB-493+ Suggested PCB Layout (PL-288)



Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuits' applicable established test performance criteria and measurement instructions.
- C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp

Features

- wide bandwidth, 1700 to 6000 MHz
- useable to 8000 MHz
- low conversion loss, 6.2 dB typ.
- IF, DC to 2000 MHz
- LTCC double balanced mixer
- aqueous washable
- low cost
- low profile, 0.095"
- protected by US Patent 7,027,795 & 8,749,989

Applications

- PCN
- defense & weather radar
- WCDMA
- defense communications

Electrical Specifications (T_{AMB}=-40°C to 85°C)

FREQUENCY (MHz)		CONVERSION LOSS (dB)			LO-RF ISOLATION (dB)		LO-IF ISOLATION (dB)		IP3 at center band (dBm)
LO/RF f _L -f _U	IF	$\bar{X}$	σ	Max.	Typ.	Min.	Typ.	Min.	Typ.
1700-4400	DC-2000	6.9	0.1	8.5*	32	25	17	—	15
4400-6000	DC-2000	6.0	0.1	8.5*	22	18	15	—	15



1 dB COMPR. +9 dBm typ.

*Conversion loss at 30 MHz IF, increases with IF frequency. See Graphs

Typical Performance Data

Frequency (MHz)		Conversion Loss (dB)	Isolation L-R (dB)	Isolation L-I (dB)	VSWR RF Port (:1)	VSWR LO Port (:1)
RF	LO	LO +13dBm	LO +13dBm	LO +13dBm	LO +13dBm	LO +13dBm
1700.00	1730.00	6.18	33.91	19.47	2.33	3.42
1852.00	1882.00	6.14	41.44	21.06	2.97	2.63
1950.00	1980.00	6.07	39.06	21.18	3.05	2.37
2048.00	2078.00	6.17	36.29	20.34	3.23	2.14
2440.00	2470.00	5.79	30.82	17.17	2.36	1.82
2930.00	2960.00	6.94	32.17	16.63	3.97	2.79
3028.00	3058.00	7.04	32.07	16.81	4.16	3.06
3126.00	3156.00	6.98	31.54	16.89	4.07	3.31
3616.00	3646.00	7.03	31.17	16.93	3.58	4.77
3812.00	3842.00	7.23	31.05	16.38	3.15	5.18
3910.00	3940.00	7.44	32.15	15.92	2.89	5.12
4008.00	4038.00	7.41	32.79	15.36	2.65	4.55
4106.00	4136.00	6.85	32.03	16.77	2.25	5.31
4204.00	4234.00	6.89	32.59	17.02	2.25	5.44
4746.00	4776.00	7.02	24.57	16.93	2.45	2.35
4818.00	4848.00	6.79	22.91	16.94	2.50	1.92
5034.00	5064.00	6.64	20.31	16.62	2.07	1.28
5538.00	5568.00	6.51	19.98	16.79	2.28	3.45
5898.00	5928.00	7.54	22.45	13.18	3.53	8.46
6000.00	6030.00	8.18	23.35	13.31	3.95	9.62

Electrical Schematic



CASE STYLE: DZ885-2

PRICE: \$7.45 ea. QTY (10-49)

+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications











www.minicircuits.com P.O. Box 35166, Brooklyn, NY 11235-0003 (718) 934-4500 sales@minicircuits.com

REV. A
M128524
MCA1T-60MH+
DJ/RS/CP
140626

Performance Charts

MCA1T-60MH+



Notes

- Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp

