





剥线尺寸
stripping dimension



产品型号 type	电缆型号 cable type
BNC-KYB3	SFT-50-3-1-RG402/U

Electrical Characteristics:

- Characteristic Impedance: 50 Ω
- Frequency range: DC~4.0Ghz
- Contact resistance
Center conductor: $\leq 1.5 \text{ m}\Omega$
Out conductor: $\leq 0.2 \text{ m}\Omega$
- Insulation resistance: $\geq 5000 \text{ M}\Omega$
- Insulator withstanding: 1500V
- VSWR: ≤ 1.4
- Durability: 500cycles

主要性能指标:

- 特性阻抗: 50 Ω
- 频率范围: DC~4.0Ghz
- 接触电阻:
中心导体: $\leq 1.5 \text{ m}\Omega$
外导体: $\leq 0.2 \text{ m}\Omega$
- 绝缘电阻: $\geq 5000 \text{ M}\Omega$
- 介质耐压: 1500V
- 电压驻波比: ≤ 1.4
- 插拔次数: 500次

Application: MIL-C-39012/16E


执行标准: MIL-C-39012/16E

Material&Finishing

- Center contact :
Female: phosphor bronze, gold plated
- Bodies and other metal parts:
brass, nickel or gold plated
- Insulators: PTFE

材料和镀层

- 中心接触件:
插孔: 锡磷青铜, 镀金
- 壳体和其它金属零件: 黄铜, 镀镍或镀金
- 绝缘子: 聚四氟乙烯

		SCALE		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE mm, TOLERANCES ARE FRACTIONS DECIMALS ANGLES .X± .15 ±1° .XX± .05 .XXX±
		1.5:1		
		NAME	DATE	RF COAXIAL CONNECTOR 西安富士达科技股份有限公司 XI'AN FORSTAR S&T CO.,LTD.
DRAWN				
CHECKED				
APPROVED				