



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: ttsales@mail.taisaw.com Web: www.taisaw.com

Approval Sheet For Product Specification

Issued Date: 2003/05/16

Product Name: SAW Filter 433MHz SMD 5.0×5.0 mm

TST Parts No.:TA0286A

Customer Parts No.:_____

Company:_____

Division:_____

Approved by :_____

Date:_____

Checked by:_____Elvis Chiu

Approval by:_____Francis Chen

Date:_____2003/05/16



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

SAW Filter 433 MHz

MODEL NO.: TA0286A

REV. NO.:1

A. MAXIMUM RATING:

1. Input Power Level: 0 dB_m
2. DC voltage: 10 V
3. Operating Temperature: -10°C to +50°C
4. Storage Temperature: -40°C to +85°C


RoHS Compliant
Lead free
Lead-free soldering

B. ELECTRICAL CHARACTERISTICS:



Item		Min.	Typical	Max.
Center frequency	F _c (dB)	-	433	-
Insertion loss (F _c ±4 MHz)	IL (dB)	-	2.7	4.5
Amplitude ripple (F _c ± 4 MHz)	(dB)	-	0.7	2.5
Attenuation (Reference level from 0 dB)				
F _c - 100 ~ F _c - 40.8 MHz	(dB)	42	50	-
F _c + 40 ~ F _c + 100 MHz	(dB)	40	46	-
Source impedance	Z _s (Ω)	-	50Ω//0pF	-
Load impedance	Z _L (Ω)	-	50Ω//0pF	-

Note1. The standard definitions is in JIS C 6703


Note2.




C. Frequency Characteristics :



D. MEASUREMENT CIRCUIT:




E.OUTLINE DRAWING:



F. PACKING:

1. REEL DIMENSION



2. TAPE DIMENSION

