



REVISIONS				
ZONE	REV	DESCRIPTION	Date	APPROVED



SPECIFICATIONS

Frequency Range: 30–35 GHz
 Isolation: 18dB Min.
 Insertion loss: 1.1dB Max.
 VSWR: 1.35:1 Max.
 Circulator Power: 25W Avg.
 Operating Temperature: –10°C to +60°C

MATERIAL: 		 MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://www.mcli.com		SCALE: N/A	
				SHEET: N/A	
UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR [mm] (MILLIMETERS) FRACTIONS: $\pm 1/64$ DECIMALS: $\pm .01 \pm .005$ ANGLE: $\pm 1/2^\circ$		DRAWING TITLE: COAXIAL CIRCULATOR			
		PART NO. CS-126			
DRAWN: Paiboon Luekhamhan DATE: 03-01-2010		DATE: 03-01-2010 PROPRIETARY NOTICE: THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICROWAVE COMMUNICATIONS LABORATORIES INC. (MCLI)		CAGE CODE: OD2L5 SIZE: A REV: N/A DO NOT SCALE THE DRAWING	
APPROVED: T. Nguyen		DATE: 03-01-2010 		DWG NO. 84729	