

SHV Jack Bulkhead Connector Solder Attachment Solder Cup Terminal, .480 inch D Hole



TECHNICAL DATA SHEET

PE4499

SHV Jack Bulkhead Connector Solder Attachment Solder Cup Terminal, .480 inch D Hole

Configuration

Connector SHV Jack
Connector Specification MIL-STD-348A
Connector Interface Type Solder Cup
Cable Attachment Method (Shield/Contact) Solder
Body Style Straight
Mount Method Bulkhead

Electrical Specifications

Frequency Range, MHz

Impedance, Ohms

Maximum VSWR

Maximum Operating Voltage, Volts

Dielectric Withstanding Voltage, Vrms

DC to 300

50

3,500

5,000

Mechanical Specifications

Temperature

Operating Range, deg C -65 to +165

Size

 Length, in [mm]
 1.78 [45.21]

 Width/Dia., in [mm]
 0.689 [18]

 Weight, lbs [g]
 0.041 [18.6]

Connector

Type SHV Jack
Contact Material and Plating Brass, Gold
Contact Plating Specification 30μ in. minimum
Body Material and Plating Brass, Nickel
Body Plating Specification 100μ in. minimum
Dielectric Type Teflon

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

Plotted and Other Data

Notes: Values at 25 °C, sea level

URL: http://www.pasternack.com/shv-jack-standard-solder-cup-terminal-connector-pe4499-p.aspx

SHV Jack Bulkhead Connector Solder Attachment Solder Cup Terminal, .480 inch D Hole from Pasternack Enterprises has same day shipment for domestic and International orders. We maintain 99% availability of the industry's broadest selection of RF, microwave and fiber optic products.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



PE4499 CAD DrawingSHV Jack Bulkhead Connector Solder Attachment Solder Cup Terminal, .480 inch D Hole

