

Reverse Polarity SMA Female to N Male Adapter



TECHNICAL DATA SHEET

PE9733

Reverse Polarity SMA Female to N Male Adapter

Configuration

Connector 1 SMA Female Reverse Polarity

Impedance 150 OhmsConnector 2N MaleImpedance 250 OhmsAdapter DesignStandardBody StyleStraight

Mechanical Specifications

Size

Length, in [mm] 1.2 [30.48] Width/Dia., in [mm] 0.8 [20.32]

Connector 1

Type SMA Female Reverse Polarity

Inner Conductor Material and Plating Gold
Body Material and Plating Brass, Nickel

Dielectric Type PTFE

Connector 2

Type N Male Inner Conductor Material and Plating Gold

Coupling Nut Material and Plating

Body Material and Plating

Brass, Nickel

Brass, Nickel

Dielectric Type

PTFE

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

Plotted and Other Data

Notes: Values at 25 °C, sea level

URL: http://www.pasternack.com/sma-female-n-male-straight-adapter-pe9733-p.aspx

Reverse Polarity SMA Female to N Male Adapter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



PE9733 CAD Drawing

Reverse Polarity SMA Female to N Male Adapter

