

Specifications


Parameter	Unit	Min	Typical	Max
Center Frequency (F0)	MHz		367.5	
Bandwidth (B)	MHz		65	
-3 dB Bandwidth (B3)	MHz	71.2	71.7	
-40 dB Bandwidth (B40)	MHz		81.6	82
Delay (T0)	μsec	3.64	3.673	3.7
Insertion Loss (IL)	dB		26.4	28
Amplitude Ripple	dB p-p		0.4	1
Phase Ripple	deg p-p		3.2	6
Rejection	dB	48	52	
Spurious for $ t-T0 > .9T0$	dB		-52	-50
Substrate Material	128YX-LN			

Notes:

- Center Frequency (F0) and Bandwidth (B) are defined, not measured.
- Insertion Loss is the minimum loss for $|f-F0| < .5B$
- Ripple spec applies to the $|f-F0| < .4B$, and is doubled for $.4B < |f-F0| < .5B$
- Rejection spec applies to $(B40 \text{ Spec} - B/2) < |f-F0| < F0/2$
- Specifications are at 22C only. Unit will operate undamaged from -54C to 125C with shifts $dF0 = -x \cdot F0$, $dT0 = x \cdot T0$, where $x = 75E-6 \cdot (\text{temperature} - 22C)$

Typical Performance


Frequency Response
(Best Fit Linear Phase Removed)



10 dB/div, 1 dB/div, 10 deg/div, 12.5 MHz/div


Impulse Response

FFT(Frequency Response * Cos(0.5 * PI * MIN(1, MAX(0, |f-F0| * 2.2 / 65 - 1.1)))^2)




10 dB/div, 0.4 us/div

Package Outline



Matching



Matched S-parameters available at www.phonon.com