Surface Mount

RF Transformer

0.3 to 120 MHz

Features

good return loss

Applications

 VHF receivers/transmitters • impedance matching

• also available with surface mount gull wing (KK81) plug-in (X65) leads

CASE STYLE: W38 PRICE: \$4.95 ea. QTY (1-9)

T13-1T+

+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications


Maximum Ratings

Operating Temperature	-20°C to 85°C		
Storage Temperature	-55°C to 100°C		
RF Power	0.25W		
DC Current	30mA		
Permanent damage may occur if any	of these limits are exceede		


Pin Connections

PRIMARY DOT	4
PRIMARY	6
SECONDARY DOT	3
SECONDARY	1
SECONDARY CT	2
NOT USED	5

Outline Drawing




NOTE: PIN NUMBERS DO NOT APPEAR ON UNIT, FOR REFERENCE ONLY. INDEX MARK NEAR PIN 6.



Outline Dimensions (inch)

F
.020
0.51
wt
grams
0.50

Config. A




Transformer Electrical Specifications


RATIO	FREQUENCY (MHz)	INSERTION LOSS*		
		MHz	MHz	MHz
13	0.3-120	0.3-120	0.7-80	5-20

*Insertion Loss is referenced to mid-band loss, 0.8 dB typ.

Typical Performance Data

	QUENCY (IHz)	INSERTION LOSS (dB)	INPUT R. LOSS (dB)	
0	.30	2.14	8.01	
0	.70	1.54	11.30	
4	.00	0.95	14.78	
8	.00	0.89	15.23	
16	.00	0.88	14.87	
38	.00	1.03	12.35	
65	.00	1.33	9.47	
88	.00	1.64	7.64	
108	.00	1.95	6.44	
120	.00	2.15	5.82	





- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.

 B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.

 C. The parts covered by this specification document are subject to Mini-Circuit satandard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp